

SPECIFICATIONS

HIGHBAYS

HOUSING

- One-piece fiberglass housing
- Poured, closed-cell gasket
- Rugged, corrosion-resistant
- 5VA flammability rating
- Stainless steel latches and mounting brackets
- Polyethylene molded end plugs for use as knockouts
- Pressure wash up to 1500 PSI

ELECTRICAL

- Quad Tap (QT) - 120-277V
- 0-10V Dimmable driver standard
- 347-480V Driver available
- Max Operating Temperature: 45°C (113°F)

OPTICAL SYSTEM

- Injection molded diffuser
- Lenses available in clear or frosted, polycarbonate or acrylic
- Color temps offered in 30K - 50K

MOUNTING

- Easy access to wiring compartment and driver via removable gear tray
- Zinc-plated mounting straps standard
- Stainless steel V-Hook mounting brackets optional
- Suitable for cable mount, ceiling mount, and dual pendant mount

CODE COMPLIANCE

- cETLus Listed for Wet Locations
- IP65 / IP66 / IP67 Rated
- NEMA 4X Listed
- RoHS Compliant

WARRANTY

- 5 Year



HB9-LED LED Vaportight Highbay

ORDERING INFORMATION

MODEL#	Wattage	Driver	CCT	Lens
HB9	60L (60W, 6675 Lm)	QT (120-277V)	30K	CAL (Clear Acrylic)
	80L (80W, 8730 Lm)	480V (347-480V)	35K	FAL (Frosted Acrylic)
	100L (100W, 11,100 Lm)		40K	CPL (Clear Polycarbonate)
	120L (120W, 13,350 Lm)		50K	FPL (Frosted Polycarbonate)
	140L (140W, 15,550 Lm)			
	150L (150W, 16,500 Lm)			
	180L (180W, 20,000 Lm)			

OPTIONS (Factory Installed)

Sensor

- OCS - Occupancy Sensor
- OCSWL - Wet Location Occupancy Sensor
- OCSCW - Cold Weather Occupancy Sensor
- OCSD - 0-10V Dimming Occupancy Sensor
- OCSM - Internal Microwave Occupancy Sensor
- PC1 - 120V Photocell
- PC2 - 277V Photocell

Battery Backup

- EM5 - 5W Battery Backup (850 Lumens)
- EM10 - 10W Battery Backup (1700 Lumens)

Cords

- CS6 - 6' 3-Wire Cordset
- CS12 - 12' 3-Wire Cordst

ACCESSORIES (Order Separately)

- HB9-VHOOK - V-Hook Brackets (2) - order two per fixture
- HB9-CMB - Ceiling Mounting Bracket (2)
- HB9-CMK - 120" Mounting Cables (2)

