

SPECIFICATIONS

HOUSING

- Heavy duty aluminum housing
- Gray painted finish

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- 4KV Surge Protection
- Operating Temperature: -40°C (-40°F) - 55°C (130°F)

OPTICAL SYSTEM

- Impact resistant clear or ribbed lenses available
- IC current controlled LED circuits
- CRI > 74
- 3000K, 4000K, or 5000K

MOUNTING

- Stainless steel bracket for ceiling mount
- Enclosure attached to back brackets for pendant mount, chain mount, or adjustable wall mount

CODE COMPLIANCE

- UL Listed for Wet Locations
- CSA Listed
- Class I, Div II, Groups A, B, C, & D
- Class II, Div II, Groups F & G
- Class III
- IP66 Rated
- CE & RoHS Compliant
- IK10

WARRANTY

- 5 year warranty
- 10 year warranty



HLVT2-F LED Hazardous Location Fixture

CATALOG #	Wattage	Size	Lumens	Lens
HLVT2-F-2X36L-QT-50K-CL	36W	2'	4,212 Lumens	Clear
HLVT2-F-2X36L-QT-50K-DL	36W	2'	3,456 Lumens	Diffused
HLVT2-F-4X36L-QT-50K-CL	36W	4'	4,680 Lumens	Clear
HLVT2-F-4X36L-QT-50K-DL	36W	4'	3,888 Lumens	Diffused
HLVT2-F-4X56L-QT-50K-CL	56W	4'	6,944 Lumens	Clear
HLVT2-F-4X56L-QT-50K-DL	56W	4'	5,824 Lumens	Diffused

OPTIONS (Factory Installed)

30K	-	3000K (replaces 50K)
40K	-	4000K (replaces 50K)
10YR	-	10 Year Warranty

ACCESSORIES (Order Separately, Ships on Side)

HLVT2-F-PPM	-	Pendant Pole Mount
HLVT2-F-PCM	-	Pendant Chain Mount
HLVT2-F-CMO	-	Ceiling Mount
HLVT2-F-BCM	-	Beam Clamp Mount
HLVT2-F-PMO	-	Pole Mount
HLVT2-F-ACM	-	Adjustable Ceiling Mount
HLVT2-F-WMO	-	Wall Mount
HLVT2-F-AWM	-	Adjustable Wall Mount

