

SPECIFICATIONS

MULTIFAMILY

HOUSING

- Aluminum housing
- Available in white or black finish
- 8^{6/7}" H x 5^{3/4}" W x 6" D

ELECTRICAL

- 120-277V
- Power Factor >.9
- THD <20%
- Efficacy: 75 LP
- Triac dimmable at 120V
- 0-10V dimming at 120-277V
- Operating Temperature: -13°F (-25°C)- 113°F(45°C)

ILLUMINATION

- Clear glass lens
- CRI ≥ 80
- MCT (3000K/4000K/5000K)
- Beam Angle: 25°
- 70,000 hours @L₇₀

MOUNTING

- Ceiling Mount

CODE COMPLIANCE

- IP40 suitable for damp locations

WARRANTY

- 5 year warranty



OC20-W Wattage and Color Selectable Cylinder

ORDERING INFORMATION

CATALOG #	Description
OC20-W-1L-QT-MCT-*	21W/28W/35W, 120-277V, 1575 / 2100 / 2625 Lm, 30K/40K/50K
*Select Color: BK-Black WH-White	

Options (Factory Installed)

- EM - Emergency Backup with Extension Cylinder

ACCESORIES (SHIPS ON SIDE)

OC-6-AG	- 6" Anodized Gold Ceiling Mount Cylinder Trim
OC-6-BN	- 6" Brushed Nickel Ceiling Mount Cylinder Trim
OC-UPL	- Uplight Kit
OC-WPCKW	- White Weatherproof Conversion Kit for Cord or Down-Rod
OC-WPCKB	- Black Weatherproof Conversion Kit for Cord or Down-Rod
OC-8FT-WH	- White 8' 5-Wire Suspension Cable and Canopy Set
OC-6-HCAG	- 6" Anodized Gold Ceiling Mount Cylinder Honeycomb Diffuser Kit
OC-6-HCBN	- 6" Brushed Nickel Ceiling Mount Cylinder Honeycomb Diffuser Kit
OC-8FT-BK	- Black 8' 5-Wire Suspension Cable and Canopy Set
OC-8FT-WH	- White 8' 5-Wire Suspension Cable and Canopy Set
OC-UNV18-BK	- Black 5-Wire Universal Swivel w/ Rod Kit (18" or 36")
OC-UNV18-WH	- White 5-Wire Universal Swivel w/ Rod Kit (18" or 36")
OC-UNV24-BK	- Black 5-Wire Universal Swivel w/ Rod Kit (24" or 48")
OC-UNV24-WH	- White 5-Wire Universal Swivel w/ Rod Kit (24" or 48")

