

SPECIFICATIONS

INDOOR

HOUSING

- Die-formed cold rolled steel housing
- Diffuser self-aligns and hinges from either side for easy maintenance
- Available in 2', 4', and 8' housings

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- Dimmable driver standard

OPTICAL SYSTEM

- Clear acrylic diffuser with prismatic bottom and ribbed linear sides
- CRI >80
- Offered in 30K, 35K, 40K, 50K

MOUNTING

- Can be surface, stem, or chain mounted

CODE COMPLIANCE

- cETLus Listed
- Meets UL Requirements
- ARRA Compliant

WARRANTY

- 5 Year
- 10 Year Warranty available

ORDERING INFORMATION

MODEL#	Length	Lumens
WA1-2x20L-QT-*	2'	2,100 Lumens
WA1-2x24L-QT-*	2'	2,500 Lumens
WA1-2x28L-QT-*	2'	2,800 Lumens
WA1-2x30L-QT-*	2'	3,060 Lumens
WA1-2x32WL-QT-*	2' (4 Rows)	3,450 Lumens
WA1-2x48WL-QT-*	2' (4 Rows)	5,000 Lumens
WA1-2x57WL-QT-	2' (4 Rows)	5,700 Lumens
WA1-4x32L-QT-*	4' (2 Rows)	3,450 Lumens
WA1-4x48L-QT-*	4' (2 Rows)	5,000 Lumens
WA1-4x57L-QT-	4' (2 Rows)	5,700 Lumens
WA1-4x60L-QT-	4' (2 Rows)	6,000 Lumens
WA1-4x72L-QT-	4' (2 Rows)	7,000 Lumens
WA1-4x48WL-QT-*	4' (4 Rows)	5,000 Lumens
WA1-4x60WL-QT-	4' (4 Rows)	5,041 Lumens
WA1-4x65WL-QT-	4' (4 Rows)	7,000 Lumens
WA1-4x72WL-QT-	4' (4 Rows)	8,200 Lumens
WA1-4x97WL-QT-	4' (4 Rows)	9,600 Lumens
WA1-4x114WL-QT-	4' (4 Rows)	10,800 Lumens
WA1-8x48L-QT-*	8' (2 Rows)	5,000 Lumens
WA1-8x65L-QT-*	8' (2 Rows)	6,000 Lumens
WA1-8x97L-QT-*	8' (2 Rows)	9,600 Lumens
WA1-8x114L-QT-*	8' (2 Rows)	10,800 Lumens

Specify 30K, 35K, 40K, or 50K

OPTIONS (Factory Installed)

EM5	- LED EM Ballast (5W, 850 Lumens)
EM7	- LED EM Ballast (7W, 1300 Lumens)
EM10	- LED EM Ballast (10W, 1700 Lumens)
CS6	- 18/3 6' Cordset
WP6	- 6', 3-Wire Whip
10YR	- Ten Year Warranty



WA1-LED LED Wraparound

