

## SPECIFICATIONS

INDOOR

### HOUSING

- Steel Housing
- Easy installation in new construction or retrofit

### ELECTRICAL

- Quad Tap (QT) - 120-277V
- 0-10V dimmable driver standard
- 347-480V driver available

### OPTICAL SYSTEM

- PMMA Lens
- CRI >82
- Linear acrylic diffuser
- Lumen Range: 5000 - 14,500 Lm
- Available in 30K, 35K, 40K, and 50K

### CODE COMPLIANCE

- cETLus Listed
- ARRA Listed
- RoHS Compliant

### WARRANTY

- 5 Year



## WA8 LED Rounded Wraparound

## ORDERING INFORMATION

MODEL#	LengthxWattage	Driver	CCT	Lens
WA8	4X32L (5000 Lm)	QT	30K	RF (Ribbed Frosted)
	4X48L (7200 Lm)	480V	35K	RC (Ribbed Clear)
	4X72L (11,000 Lm)		40K	
			50K	
	8X48L (7200 Lm)			
	8X65L (9700 Lm)			
	8X97L (14,500 Lm)			

### OPTIONS (Factory Installed)

EM5	- 5W 600 Lumen Battery
EM7	- 7W 840 Lumen Battery
EM10	- 10W 1200 Lumen Battery
WH3	- 3-Wire harness, including white, black, and green
WH4	- 4-Wire harness, including white, black, green, and blue for emergency battery backup
WH5	- 5-Wire harness, including white, black, green, violet, and gray
WP6	- 3-Wire 6' Whip

