

SPECIFICATIONS

OUTDOOR

HOUSING

- Heavy duty die cast aluminum housing
- Bronze powdercoat bronze finish standard
- Other finishes available with extended lead times
- Corrosion resistant housing and hardware
- OxyShield 9-stage anti-oxidation process
- Silicone rubber gasket
- EPA rating: 0.9

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- 480V available
- Operating Temperature: -40°C (-40°F) - 65°C (150°F)
- 0-10V dimmable driver

OPTICAL SYSTEM

- UV-resistant polycarbonate lens
- High quality heat sinks for temperature control
- IC current controlled LED circuits
- 100,000 Hours @ L₇₀
- CRI > 80
- PF > 0.90
- THD < 10%
- 3000K, 4000K and 5000K available

MOUNTING

- Arm mount, slipfitter, or trunion mounts available

CODE COMPLIANCE

- UL Listed for Wet Locations
- IP67
- Meets DLC Requirements

WARRANTY

- 10 Year



AL33-T LED Dual Headed Area Light

ORDERING INFORMATION

CATALOG #	Wattage	Lumens	Color	Distribution
AL33-T-60L-QT-50K-T3	60W	9,831	5000K	Type III
AL33-T-60L-QT-50K-T3-HO	60W	11,092	5000K	Type III
AL33-T-60L-QT-50K-T5	60W	9,943	5000K	Type V
AL33-T-60L-QT-50K-T5-HO	60W	11,124	5000K	Type V
AL33-T-90L-QT-50K-T3	90W	14,747	5000K	Type III
AL33-T-90L-QT-50K-T3-HO	90W	16,637	5000K	Type III
AL33-T-90L-QT-50K-T5	90W	14,915	5000K	Type V
AL33-T-90L-QT-50K-T5-HO	90W	16,655	5000K	Type V
AL33-T-120L-QT-50K-T3	120W	19,827	5000K	Type III
AL33-T-120L-QT-50K-T3-HO	120W	22,184	5000K	Type III
AL33-T-120L-QT-50K-T5	120W	20,427	5000K	Type V
AL33-T-120L-QT-50K-T5-HO	120W	22,192	5000K	Type V
AL33-T-150L-QT-50K-T3	150W	24,578	5000K	Type III
AL33-T-150L-QT-50K-T3-HO	150W	27,793	5000K	Type III
AL33-T-150L-QT-50K-T5	150W	24,741	5000K	Type V
AL33-T-150L-QT-50K-T5-HO	150W	27,742	5000K	Type V

OPTIONS (Factory Installed)

T4	- Type IV
30K	- 3000K (5000K standard)
40K	- 4000K (5000K standard)
57K	- 5700K (5000K standard)
480V	- 480V(replaces QT)
WH	- White Housing
BLK	- Black Housing
GR	- Gray Housing
CC	- Custom Color
PC	- Photocell
OCS	- Occupancy Sensor
EBLED	- Emergency Ballast

ACCESSORIES (Order Separately, Ships on Side)

AL33-T-ARM6	- 6" Mounting Arm
AL33-T-SF	- Slip Fitter
AL33-T-SB	- Trunion Mount

