

SPECIFICATIONS

OUTDOOR

HOUSING

- Heavy duty die cast aluminum housing
- Open air heat sinks
- Bronze or white housing available

ELECTRICAL

- Quad Tap (120/-277Vac)
- 277-480V also available
- 0-10V Dimmable Driver Standard
- Operating Temperature: -4°F - 113°F (-20°C - 45°C)
- Surge Protection: 4kV-10kV

OPTICAL SYSTEM

- MCT (Selectable): 30K / 40K / 50K
- Type III standard, also available in Types II, IV, and V
- 50,000 hours @ L₇₀
- CRI>70
- Power factor > .90
- THD < 15%

MOUNTING

- Trunion Mount standard
- Slip Fitter, round/square pole, trunnion, yoke, and universal mounts

CODE COMPLIANCE

- cULus Listed for Wet Locations
- DLC Premium Listed
- RoHS Compliant
- FCC Compliant

WARRANTY

- 5 Year



AL34-S-MCT LED Wattage and Color Selectable Area Light

ORDERING INFORMATION

CATALOG#	Wattage	Lumens	Distribution
AL34-S-1L-QT-MCT-T3	100W / 150W / 200W	14,000 / 21,000 / 28,000 Lm	Type III
AL34-S-2L-QT-MCT-T3	200W / 240W / 300W	28,000 / 33,600 / 42,000 Lm	Type III

OPTIONS (Factory Installed)

480V	- 277-480V Driver (replaces QT in part number)
T2	- Type II Distribution (replaces T3 in part number)
T4	- Type IV Distribution (replaces T3 in part number)
T5	- Type V Distribution (replaces T3 in part number)
WH	- White Housing

ACCESSORIES (Order Separately, Ships on Side)

AL34-S-GSS	- Glare Shield (for 1L models)
AL34-S-GSL	- Glare Shield (for 2L models)
AL34-S-SB	- Trunnion Mount
AL34-S-SF	- Slip Fitter
AL34-S-PM	- Pole Mount
AL34-S-ARM	- Universal Mount (slipfitter and pole mount)
AL34-S-YM	- Yoke Mount
AL-S-PC	- Photocell Sensor
AL-S-MOCS	- 12V DC Microwave BiLevel Daylight Sensor
REM6-S	- Sensor Remote Control with LCD Display



AL34-S-SF



AL34-S-SB



AL34-S-PM



AL34-S-ARM



AL34-S-YM

