

SPECIFICATIONS

MULTI FAMILY

HOUSING

- Decorative extruded aluminum round housing
- Available in bronze or black
- Corrosion resistant housing and hardware
- OxyShield 9-stage anti-oxidation process
- Silicone rubber gasket

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- Operating Temperature: -40°C (-40°F) - 40°C (104°F)

OPTICAL SYSTEM

- Cone and Louver reflectors available
- Clear or Frosted lens
- High quality heat sinks for temperature control
- IC current controlled LED circuits
- CRI ≥ 70
- Color Selectable: 30K/40K/50K
- Wattage Selectable: 12W - 22W

MOUNTING

- Mounts with 7.5" anchor bolts, included

CODE COMPLIANCE

- cULus Listed for Wet Locations
- IP65 Rated

WARRANTY

- 5 Year



BRLD-W Round Flat Dome LED Bollard

ORDERING INFORMATION

CATALOG #	Reflector	Lens
BRLD-W-ARC-1L-QT-MCT	Cone	Clear
BRLD-W-ARF-1L-QT-MCT	Cone	Frosted
BRLD-W-CRC-1L-QT-MCT	Louver	Clear

OPTIONS (Factory Installed)

BLK - Black Housing (bronze standard)

Wattage Selectable	Color Selectable	Lumen
12W	3000K	1,560 Lumens
	4000K	1,620 Lumens
	5000K	1,680 Lumens
16W	3000K	2,080 Lumens
	4000K	2,160 Lumens
	5000K	2,240 Lumens
22W	3000K	2,860 Lumens
	4000K	2,970 Lumens
	5000K	3,020 Lumens

