

SPECIFICATIONS

MULTI FAMILY

HOUSING

- Decorative extruded aluminum square housing
- Available in bronze or black
- Corrosion resistant housing and hardware
- OxyShield 9-stage anti-oxidation process
- Silicone rubber gasket

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- Operating Temperature: -40°C (-40°F) - 40°C (104°F)

OPTICAL SYSTEM

- Cone reflector
- Frosted lens
- High quality heat sinks for temperature control
- IC current controlled LED circuits
- 187,000 hours @ L₇₀
- CRI ≥ 70
- Color Selectable: 30K/40K/50K
- Wattage Selectable: 12W - 22W

MOUNTING

- Mounts with 7.5" anchor bolts, included

CODE COMPLIANCE

- cULus Listed for Wet Locations
- IP65 Rated

WARRANTY

- 5 Year



BSLF-W Square LED Flat Top Bollard

ORDERING INFORMATION

CATALOG #	Lumens	Color
BSLW-F-1L-QT-MCT	1500 - 2970 Lumens	30K/40K/50K

OPTIONS (Factory Installed)

BLK - Black Housing (bronze standard)

Wattage Selectable	Color Selectable	Lumen
12W	3000K	1,500 Lumens
	4000K	1,560 Lumens
	5000K	1,620 Lumens
16W	3000K	2,000 Lumens
	4000K	2,080 Lumens
	5000K	2,160 Lumens
22W	3000K	2,750 Lumens
	4000K	2,860 Lumens
	5000K	2,970 Lumens

