

SPECIFICATIONS

INDOOR

HOUSING

- Aluminum sheet housing
- Satin coating
- Corrosion, discoloration, and scratching resistant
- Available in 1x4, 2x2, and 2x4 models
- Microwave Sensor installed

ELECTRICAL

- Quad-Tap (120-277Vac)
- 0-10V Dimmable driver standard
- Operating Temperature: -20°C (-4°F) - 45°C (113°F)

OPTICAL SYSTEM

- Anti-UV Frosted Polycarbonate Lens
- MCT (field selectable between 35K/40K/50K)
- 50,000 hours @ L₇₀
- CRI > 80
- THD < 15%
- Power Factor > 0.90

MOUNTING

- Recessed T-Bar Ceiling Mount

CODE COMPLIANCE

- cETLus Listed for Damp locations
- DLC Premium Listed
- FCC Compliant
- RoHS Compliant

WARRANTY

- 5 year



CB3-S-MCT LED Wattage and Color Selectable Basket

ORDERING INFORMATION

CATALOG #	Size	Wattage	Lumens	Color
CB3-S-14X1L-QT-MCT	1X4	25W/30W/40W	3125/3750/5000 Lm	35K/40K/50K
CB3-S-22X1L-QT-MCT	2X2	15W/18W/24W	3125/3750/5000 Lm	35K/40K/50K
CB3-S-24X1L-QT-MCT	2X4	20W/25W/30W	4375/5000/6250 Lm	35K/40K/50K

OPTIONS (Ships Installed)

EM8 - 8W Emergency Battery

