

SPECIFICATIONS

OUTDOOR

FEATURES

- White aluminum housing
- Acrylic acrylic, frosted prismatic, or clear polycarbonate lenses available
- Available in 3000K and 4000K
- Wall or Ceiling Mount
- CRI > 80

ELECTRICAL

- 120VAC
- Dimmable Driver
- Operating Temperature: -40°C - 40°F

CODE COMPLIANCE

- cULus Listed for Wet Locations
- Assembled in America
- RoHS Compliant
- Energy Star Compliant

WARRANTY

- 5 year warranty

ORDERING INFORMATION

CATALOG #	Wattage	Lumens	Color
CPY1-G-13L-120V-30K-*	13W	1,140 Lumens	3000K
CPY1-G-13L-120V-40K-*	13W	1,280 Lumens	4000K
CPY1-G-14L-120V-30K-*	14W	1,430 Lumens	3000K
CPY1-G-14L-120V-40K-*	14W	1,500 Lumens	4000K
CPY1-G-22L-120V-30K-*	22W	1,950 Lumens	3000K
CPY1-G-22L-120V-40K-*	22W	2,130 Lumens	4000K

Specify Lens: FAL-Frosted Acrylic, CAL-Clear Acrylic, CPL-Clear Polycarbonate

OPTIONS (Factory Installation)

OCS - Motion Sensor



CPY1-G-LED LED Canopy Light

