

SPECIFICATIONS

MULTI-FAMILY

HOUSING

- Galvanized Steel
- Durable UV resistant non-corrosive resin frame
- UV-Stabilized acrylic lens
- Mounts to ceiling

ELECTRICAL

- 120V
- QT (120/208/240/277V)
- Dimmable driver standard

OPTICAL SYSTEM

- Frosted ribbed acrylic lens
- 50,000 hours @ L₇₀
- Offered in 3000K, and 4000K

CODE COMPLIANCE

- cULus Listed
- ARRA Compliant
- RoHS Compliant
- Energy Start Compliant

WARRANTY

- 5 Year



**CPY3
LED Canopy**

Wired

MODEL#	Wattage	Lumens	Color	Dimmable
CPY3-13L-120V-30K-*	13W	900 Lumens	3000K	Yes
CPY3-13L-120V-40K-*	13W	1000 Lumens	4000K	Yes
CPY3-14L-120V-30K-*	14W	1350 Lumens	3000K	Yes
CPY3-14L-120V-40K-*	14W	1400 Lumens	4000K	Yes
CPY3-22L-QT-40K-*	22W	1824 Lumens	4000K	No
CPY3-23L-120V-30K-*	23W	1800 Lumens	3000K	Yes
CPY3-23L-120V-40K-*	23W	1900 Lumens	4000K	Yes

*Specify Housing Color; **W**hite, **B**lack

GU Base

MODEL#	Lamps
CPY3-13L GU-120V	1x13W GU Base
CPY3-26L GU-120V	2x13W GU Base
CPY3-18L GU-120V	1x18W GU Base
CPY3-36L GU-120V	2x18W GU Base
CPY3-23L GU-120V	1x26W GU Base
CPY3-46L GU-120V	2x26W GU Base
CPY3-26L GU-120V	1x26W GU Base
CPY3-27L GU-120V	1x27W GU Base

OPTIONS (Factory Installed)

- PC - Photocell
- OCS - Motion Sensor

