

SPECIFICATIONS

MULTIFAMILY

HOUSING

- Polycarbonate base and diffuser
- Knockouts for conduit
- Available in black or white finish

ELECTRICAL

- Operating temperature: -40°C (-40°F) - 40°C (104°F)

MOUNTING

- Wall or ceiling mount

CODE COMPLIANCE

- cULus Listed for wet locations
- RoHS compliant
- Energy Star qualified

WARRANTY

- 5 Year



CPY4-G
Canopy

CATALOG#	Housing	Illumination	Lumens	Color	Voltage	Dimmable
CPY4-G-R-13L-120V-30K-*#	Round	13W	1140 Lm	3000K	120V	Yes
CPY4-G-S-13L-120V-30K-*#	Square	13W	1140 Lm	3000K	120V	Yes
CPY4-G-R-13L-120V-40K-*#	Round	13W	1280 Lm	4000K	120V	Yes
CPY4-G-S-13L-120V-40K-*#	Square	13W	1280 Lm	4000K	120V	Yes
CPY4-G-R-14L-120V-30K-*#	Round	14W	1430 Lm	3000K	120V	Yes
CPY4-G-S-14L-120V-30K-*#	Square	14W	1430 Lm	3000K	120V	Yes
CPY4-G-R-14L-120V-40K-*#	Round	14W	1500 Lm	4000K	120V	Yes
CPY4-G-S-14L-120V-40K-*#	Square	14W	1500 Lm	4000K	120V	Yes
CPY4-G-R-22L-120V-30K-*#	Round	22W	1950 Lm	3000K	120V	Yes
CPY4-G-S-22L-120V-30K-*#	Square	22W	1950 Lm	3000K	120V	Yes
CPY4-G-R-22L-120V-40K-*#	Round	22W	2130 Lm	4000K	120V	Yes
CPY4-G-S-22L-120V-40K-*#	Square	22W	2130 Lm	4000K	120V	Yes
CPY4-G-R-22L-QT-30K-*#	Round	22W	1704 Lm	3000K	120-277V	No
CPY4-G-S-22L-QT-30K-*#	Square	22W	1704 Lm	3000K	120-277V	No
CPY4-G-R-22L-QT-40K-*#	Round	22W	1824 Lm	4000K	120-277V	No
CPY4-G-S-22L-QT-40K-*#	Square	22W	1824 Lm	4000K	120-277V	No
CPY4-G-R-80I-120V-*#	Round	2x40W Medium Base			120V	No
CPY4-G-S-80I-120V-*#	Square	2x40W Medium Base			120V	No
CPY4-G-R-13GU-120V-*#	Round	1x13W GU24 Base			120V	No
CPY4-G-S-13GU-120V-*#	Square	1x13W GU24 Base			120V	No
CPY4-G-R-26GU-120V-*#	Round	2x13W GU24 Base			120V	No
CPY4-G-S-26GU-120V-*#	Square	2x13W GU24 Base			120V	No
CPY4-G-R-18GU-120V-*#	Round	1x18W GU24 Base			120V	No
CPY4-G-S-18GU-120V-*#	Square	1x18W GU24 Base			120V	No
CPY4-G-R-36GU-120V-*#	Round	2x18W GU24 Base			120V	No
CPY4-G-S-36GU-120V-*#	Square	2x18W GU24 Base			120V	No

*Specify Housing: **White**, **Black**

#Specify Lens: **White**, **FRsted**

OPTIONS (Factory Installed)

EM	- Emergency Battery (Only available for LED models)
OCS	- Occupancy Sensor (Only available for LED models)
30K	- 3000K Dimmable LED Lamp (Only available for Incandescent units)
40K	- 4000K Dimmable LED Lamp (Only available for Incandescent units)
27K	- 2700K (Only available for CFL base units)

