

SPECIFICATIONS

INDOOR

HOUSING

- White finish standard (black available for 4' models)
- Housings offered in 2', 4' and 8'
- 6.5' adjustable hanging cables included
- 6.5' 5-wire power feed cable included
- Wire harness connection kit included for connecting power between fixtures

ELECTRICAL

- Quad Tap (120-277V)
- 0-10V Dimmable Driver Standard
- Operating Temperature: -20°C (-4°F) - 40°C (104°F)
- Power factor > 95

OPTICAL SYSTEM

- MCT (3000K, 4000K, 5000K)
- 50,000 hours @ L₇₀
- CRI > 80
- Beam Angle: 100°

CODE COMPLIANCE

- cETLus Listed for Damp Locations
- DLC Premium listed

WARRANTY

- 5 Years



DIDL-K-MCT LED Direct/Indirect Linear Fixture

ORDERING INFORMATION

CATALOG#	Size	Wattage	Lumens	Voltage	CCT	Finish
DIDL-K-2X25L-QT-MCT	2'	25W	3250 lms	120-277V	30K/40K/50K	White
DIDL-K-4X50L-QT-MCT-BK	4'	50W	6500 lms	120-277V	30K/40K/50K	Black
DIDL-K-4X50L-QT-MCT	4'	50W	6500 lms	120-277V	30K/40K/50K	White
DIDL-K-8X100L-QT-MCT	8'	100W	13,000 lms	120-277V	30K/40K/50K	White

ACCESSORIES (Order Separately, Ships on Side)

DIDL-K-LJ - L-Shaped Joint (12W, MCT)

DIDL-K-TJ - T-Shaped Joint (12W, MCT)

DIDL-K-XJ - X-Shaped Joint (12W, MCT)

DIDL-K-SMB - Surface Mount Bracket

DIDL-K-WB - Wall Mounting Bracket



