

SPECIFICATIONS

MULTI-FAMILY

HOUSING

- Fade and rust resistant composite construction
- Offered in white or black finishes

OPTICAL SYSTEM

- Clear polycarbonate and glass diffusers available
- Offered in dedicated LED, screw-in LED, incandescent, and fluorescent

ELECTRICAL

- 120V
- QT (120-277V) - 11L model only

MOUNTING

- Wall mount only

CODE COMPLIANCE

- cULus Listed for Wet Locations
- Made in America
- RoHS Compliant
- Energy Star Compliant

WARRANTY

- 1 Year






EL1-G-1

EL1-G-2



EL1-G-3

EL1-G Entry Light



ORDERING INFORMATION

MODEL#	Light Source (description)	Body	Diffuser
EL1-G-1	11L-QT-40K (11.3W LED, 912 Lumens, 4000K, 120-277V)	BL (Black)	CLP (Clear Prismatic)
EL1-G-2	13L-120V-30K (13W LED, 1140 Lumens, 3000K, 120V)	WH (White)	WHA (White Acrylic)
EL1-G-3	13L-120V-40K (13W LED, 1280 Lumens, 4000K, 120V)		
60W-120V (60W Max Incandescent, Medium Base, 120V)			
13CFL-120V (13W CFL GU24 Base, 120V)			
18CFL-120V (18W CFL GU24 Base, 120V)			

ACCESSORIES (Order Separately, Ships on Side)

27K	- 2700K CFL Lamp (use with CFL models)
30K	- Dimmable LED Lamp, 3000K, A19/E26 (use with incandescent model)
40K	- Dimmable LED Lamp, 4000K, A19/E26 (use with incandescent model)
PC	- Photocell (not available on 11L model)