

SPECIFICATIONS

MULTI-FAMILY

HOUSING

- Fade and rust resistant composite construction
- Offered in white or black finishes

OPTICAL SYSTEM

- Clear polycarbonate and glass diffusers available
- Offered in dedicated LED, screw-in LED, incandescent, and fluorescent

ELECTRICAL

- 120V
- QT (120-277V) - 11L model only

MOUNTING

- Wall mount only

CODE COMPLIANCE

- cULus Listed for Wet Locations
- Made in America
- RoHS Compliant
- Energy Star Compliant

WARRANTY

- 1 Year



EL2-G
Entry Light

ORDERING INFORMATION

CATALOG #	Light Source (description)	Body	Diffuser
EL2-G	11L-QT-40K (11.8W LED, 912 Lumens, 4000K, 120-277V)	BL (Black)	CLP (Clear Poly.)
	13L-120V-30K (13W LED, 1140 Lumens, 3000K, 120V)	WH (White)	CLG (Clear Glass)
	13L-120V-40K (13W LED, 1280 Lumens, 4000K, 120V)		
	60W-120V (60W Max Incandescent, Medium Base, 120V)		
	13CFL-120V (13W CFL GU24 Base, 120V)		
	18CFL-120V (18W CFL GU24 Base, 120V)		

ACCESSORIES (Order Separately, Ships on Side)

LLP-27K-G	-	2700K CFL Lamp (use with CFL models)
LLP-30K-G	-	Dimmable LED Lamp, 3000K, A19/E26 (use with incandescent model)
LLP-40K-G	-	Dimmable LED Lamp, 4000K, A19/E26 (use with incandescent model)
PC	-	Photocell (not available on 11L model)

