

SPECIFICATIONS

MULTI-FAMILY

HOUSING

- Cold rolled steel housing
- Standard in Satin Nickel
- Also available in Polished Brass, White, or Oil Rubbed Bronze finishes
- Acrylic Shade
- Mounts to ceiling; pendant mounting available

ELECTRICAL

- Power Factor > 0.95
- THD < 20%

OPTICAL SYSTEM

- Acrylic bottom panel
- LED: Offered in 30K - 50K
- MCT: All in One; 30K, 35K, or 40K

CODE COMPLIANCE

- cETLus Listed for Damp Locations
- Energy Star Compliant

WARRANTY

- 5 Year



FCMP19
LED Ceiling Mount

ORDERING INFORMATION

MODEL#	Wattage	Lumens	Voltage	OD x H
FCMP19-1-#-9L-120V-*	9W	900 Lumens	120V	10.4" x 4.2"
FCMP19-1-#-11L-120V-*	11W	1000 Lumens	120V	10.4" x 4.2"
FCMP19-1-#-18L-120V-*	18W	1340 Lumens	120V	10.4" x 4.2"
FCMP19-1-#-18L-120V-MCT	18W	1340 Lumens	120V	10.4" x 4.2"
FCMP19-2-#-9L-120V-*	9W	880 Lumens	120V	11.8" x 4.2"
FCMP19-2-#-11L-120V-*	11W	1030 Lumens	120V	11.8" x 4.2"
FCMP19-2-#-18L-120V-*	18W	1430 Lumens	120V	11.8" x 4.2"
FCMP19-2-#-18L-120V-MCT	18W	1340 Lumens	120V	11.8" x 4.2"
FCMP19-3-#-23L-QT-*	23W	2267 Lumens	120-277V	14.5" x 4.6"
FCMP19-3-#-24L-QT-MCT	24W	2267 Lumens	120-277V	14.5" x 4.6"
FCMP19-4-#-28L-QT-*	28W	2600 Lumens	120-277V	16.0" x 4.9"
FCMP19-4-#-28L-QT-MCT	28W	2600 Lumens	120-277V	16.0" x 4.9"
FCMP19-5-#-35L-QT-*	35W	3364 Lumens	120-277V	17.8" x 4.9"
FCMP19-5-#-35L-QT-MCT	35W	3364 Lumens	120-277V	17.8" x 4.9"
FCMP19-6-#-40L-QT-*	40W	3500 Lumens	120-277V	20.5" x 5.0"
FCMP19-6-#-40L-QT-MCT	40W	3500 Lumens	120-277V	20.5" x 5.0"
FCMP19-7-#-40L-QT-*	40W	3450 Lumens	120-277V	24.1" x 5.0"
FCMP19-7-#-40L-QT-MVT	40W	3450 Lumens	120-277V	24.1" x 5.0"

#Specify P1, P2, or Leave Blank for Surface Mount
***Specify 30K, 35K, 40K, 50K**

OPTIONS

- OR - Oil Robbed Bronze (satin nickel standard)
- WH - White Finish (satin nickel standard)
- PB - Polished Brass (satin nickel standard)