

SPECIFICATIONS

MULTI-FAMILY

HOUSING

- Cold rolled steel housing
- Offered in White, Oil Rubbed Bronze, or Satin Nickel finishes
- Mounts to ceiling; pendant mounting optional

ELECTRICAL

- CFL: 120V
- LED: 120-277V
- Battery Backup (EBLED) and Bi-Level Lighting (BIL) available

OPTICAL SYSTEM

- Frosted Swirl Glass
- LED: Offered in 3000K standard, 3500K - 5000K optional

CODE COMPLIANCE

- cULus Listed for Damp Locations
- cETLus Listed for Damp Locations
- LED is Energy Star Listed

WARRANTY

- 5 Year



FCMP6
LED Ceiling Mount

ORDERING INFORMATION

CATALOG#	Wattage	Lumens	OD x H	Finish
FCMP6-23L-QT-30K-SN	23W	2000	15.2" x 6.7"	Satin Nickel
FCMP6-23L-QT-30K-SN-EBLED	23W	2000	15.2" x 6.7"	Satin Nickel
FCMP6-23L-QT-30K-SN-BIL	23W	2000	15.2" x 6.7"	Satin Nickel
FCMP6-23L-QT-30K-SN-BIL-EBLED	23W	2000	15.2" x 6.7"	Satin Nickel
FCMP6-46W-120V-ORB	2x23W GU24		15.2" x 6.7"	Rubbed Bronze
FCMP6-46W-120V-WH	2x23W GU24		15.2" x 6.7"	White
FCMP6-46W-120V-SN	2x23W GU24		15.2" x 6.7"	Satin Nickel

ACCESSORIES (Factory Installed)

3500K	- 3500K (3000K standard)
4000K	- 4000K (3000K standard)
5000K	- 5000K (3000K standard)
WH	- White Housing (satin nickel standard)
ORB	- Oil Rubbed Bronze Housing (satin nickel standard)

