

SPECIFICATIONS

OUTDOOR

HOUSING

- Heavy duty die cast aluminum housing
- Black powdercoat bronze finish
- White optional
- Corrosion resistant housing and hardware
- OxyShield 9-stage anti-oxidation process
- Silicone rubber gasket

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- Dimmable driver standard (120W/150W)
- Operating Temperature: -30°F (-30°C) - 130°F (54°C)

OPTICAL SYSTEM

- Glass lens
- High quality heat sinks for temperature control
- IC current controlled LED circuits
- 40-150W fixtures offered
- 100,000 Hours @ L₇₀
- CRI>70
- Available in 5700K

MOUNTING

- Provided standard with yoke mount

CODE COMPLIANCE

- UL Listed for Wet Locations
- IP65 Rated
- Meets DLC Requirements

WARRANTY

- 5 Year
- 10 Year Available

ORDERING INFORMATION


CATALOG #	Lumens	Distribution	Color
FL21-T-40AL-QT-50K-AY	4,600	Nema 7	5000K
FL21-T-40BL-QT-50K-AY	5,400	Nema 7	5000K
FL21-T-60AL-QT-50K-AY	6,900	Nema 7	5000K
FL21-T-60BL-QT-50K-AY	8,100	Nema 7	5000K
FL21-T-90AL-QT-50K-AY	10,530	Nema 7	5000K
FL21-T-90BL-QT-50K-AY	12,150	Nema 7	5000K
FL21-T-120AL-QT-50K-AY	13,800	Nema 7	5000K
FL21-T-120BL-QT-50K-AY	16,200	Nema 7	5000K
FL21-T-150AL-QT-50K-AY	17,200	Nema 7	5000K
FL21-T-150BL-QT-50K-AY	20,250	Nema 7	5000K

OPTIONS (Factory Installed)

30K	-	3000K (replaces 50K in part number)
40K	-	4000K (replaces 50K in part number)
57K	-	5700K (replaces 50K in part number)
WH	-	White Housing (extended lead time)
DIM	-	0-10V Dimmable (40W/60W/90W)
Standard on 120W & 150W		
480V	-	480V Driver (120W and 150W only)
OCS	-	Occupancy Sensor (120W and 150W only)
PC1	-	120V Photocell
PC2	-	277V Photocell
WP	-	4' Whip
10YR	-	10 Year Warranty



FL21-T
LED Flood Light



	40W	60W	90W	120W	150W
A	6.57"	8.66"	9.65"	11.61"	9.65"
B	1.57"	1.87"	1.95"	2.11"	1.95"
C	7.87"	10.43"	11.81"	13.58"	11.81"
D	8.92"	12.22"	13.95"	15.84"	13.95"
Weight	6.6lbs	7.7lbs	11.0lbs	15.4lbs	16.5lbs