

## SPECIFICATIONS

OUTDOOR

### HOUSING

- Durable die-cast housing
- Available in bronze or white finishes

### ELECTRICAL

- QT (120-277V)
- 0-10V Dimmable Driver Standard
- Built in photocell- can be turned on or off

### OPTICAL SYSTEM

- MCT: Selectable between 3000K/4000K/5000K
- CRI>80

### MOUNTING

- Knuckle and Yoke mount included (knuckle standard)
- Slip Fitter mount included for 3L model

### CODE COMPLIANCE

- UL Listed for Wet Locations
- IP65 Rated
- DLC Premium Listed


### WARRANTY

- 5 Year




## FL25-C Color Selectable LED Flood Light


Knuckle Mount



Yoke Mount



Slip Fitter Mount



Model	A	B	C	D
1L Knuckle	7"	3"	5"	3.75"
2L Knuckle	10.5"	3"	7"	2.15"
1L Yoke	7"	3"	5"	2.4"
2L Yoke	10.5"	3.25"	7"	4"
3L Slipfitter	14"	3.25"	9"	7.1"
3L Yoke	14"	3.25"	9"	4"

## ORDERING INFORMATION

CATALOG#	Wattage	Driver	CCT	Color
FL25-C	1L (15W/25W/35W) (2,224 / 3,258 / 4,796 Lm)	QT	MCT(30K/40K/50K)	BZ
	2L (50W/70W/90W) (7,415 / 9,777 / 11,896 Lm)			WH
	3L (105W/120W/150W) (15,148 / 16,590 / 20,793 Lm)			

### ACCESSORIES (Factory Installed)

FL25-C-WG1	- Wire Guard for 1L Models
FL25-C-WG2	- Wire Guard for 2L Models
FL25-C-WG3	- Wire Guard for 3L Models
FL25-C-LG1	- Vandal Shield for 1L Models
FL25-C-LG2	- Vandal Shield for 2L Models
FL25-C-LG3	- Vandal Shield for 3L Models