

SPECIFICATIONS

INDOOR

HOUSING

- Aluminum frame and steel housing backplate
- Available in 1X4, 2x2 and 2x4 models

ELECTRICAL

- Quad-Tap (120-277Vac)
- 0-10V Dimmable driver standard
- Operating Temperature: -20°C (-4°F) - 45°C (113°F)

OPTICAL SYSTEM

- Anti-UV frosted polycarbonate lens
- 5CT (field selectable between 35K/40K/50K/57K/65K)
- 50,000 hours @ L₇₀
- CRI > 83
- THD < 15%
- Power Factor > 0.90

MOUNTING

- Recessed TBar Ceiling Mount
- Optional Flange Kit and Surface mount kits available

CODE COMPLIANCE

- cETLus Listed for Damp Locations
- DLC Premium Listed

WARRANTY

- 5 Year



FP9-S-5CT LED Wattage and Color Selectable Panel

ORDERING INFORMATION

CATALOG #	Size	Wattage	Lumens	Color
FP9-S-14-1L-QT-5CT	1X4	15W - 40W	1950 - 5200 Lumens	35K - 65K
FP9-S-22-1L-QT-5CT	2X2	15W - 40W	1950 - 5200 Lumens	35K - 65K
FP9-S-24-1L-QT-5CT	2X4	25W - 50W	3250 - 6500 Lumens	35K - 65K
FP9-S-24-2L-QT-5CT	2X4	30W - 72W	3900 - 9360 Lumens	35K - 65K

OPTIONS (Ships Installed)

- | | |
|------|----------------------------|
| EM8 | - 8W LED Emergency Driver |
| EM20 | - 20W LED Emergency Driver |

ACCESSORIES (Order Separately, Ships on Side)

- | | |
|-------------|-------------------------|
| FP9-S-SMK14 | - 1x4 Surface Mount Kit |
| FP9-S-SMK22 | - 2x2 Surface Mount Kit |
| FP9-S-SMK22 | - 2x2 Surface Mount Kit |

LUMEN INFORMATION

Catalog #	Wattage	Lumens	Input Amps (A)	
			120V	277V
FP9-S-14-1L (35K)	15W	1950	0.14	0.06
FP9-S-14-1L (40K)	20W	2600	0.18	0.08
FP9-S-14-1L (50K)	25W	3250	0.23	0.10
FP9-S-14-1L (57K)	30W	3900	0.28	0.12
FP9-S-14-1L (65K)	40W	5200	0.37	0.16
FP9-S-22-1L (35K)	15W	1950	0.14	0.06
FP9-S-22-1L (40K)	20W	2600	0.18	0.08
FP9-S-22-1L (50K)	25W	3250	0.23	0.10
FP9-S-22-1L (57K)	30W	3900	0.28	0.12
FP9-S-22-1L (65K)	40W	3900	0.37	0.16
FP9-S-24-1L (35K)	25W	3250	0.23	0.10
FP9-S-24-1L (40K)	30W	3900	0.28	0.12
FP9-S-24-1L (50K)	35W	4500	0.32	0.14
FP9-S-24-1L (57K)	40W	5200	0.37	0.16
FP9-S-24-1L (65K)	50W	6500	0.46	0.20
FP9-S-24-2L (35K)	30W	3900	0.28	0.12
FP9-S-24-2L (40K)	40W	5200	0.37	0.16
FP9-S-24-2L (50K)	50W	6500	0.46	0.20
FP9-S-24-2L (57K)	60W	7500	0.55	0.24
FP9-S-24-2L (65K)	72W	9360	0.66	0.29