

SPECIFICATIONS

INDOOR

HOUSING

- Aluminum frame and steel housing backplate
- Available in 1X4, 2x2 and 2x4 models

ELECTRICAL

- Quad-Tap (120-277Vac)
- 0-10V Dimmable driver standard
- 50,000 hours @ L₇₀
- Operating Temperature: -20°C (-4°F) - 45°C (113°F)

OPTICAL SYSTEM

- Anti-UV frosted polycarbonate lens
- 5CT (field selectable between 35K/40K/50K/57K/65K)
- CRI > 80
- THD < 15%
- Power Factor > 0.90

MOUNTING

- Recessed TBar Ceiling Mount
- Optional Flange Kit and Surface mount kits available

CODE COMPLIANCE

- cETLus Listed for Damp Locations
- FCC Compliant
- DLC Premium Listed
- IP44

WARRANTY

- 5 Year



FP9-S1-5CT LED Wattage and Color Selectable Panel

ORDERING INFORMATION

CATALOG #	Size	Wattage	Lumens	Color
FP9-S1-14-1L-QT-5CT	1X4	15W - 40W	1875 - 5000 Lumens	35K - 65K
FP9-S1-22-1L-QT-5CT	2X2	15W - 40W	1875 - 5000 Lumens	35K - 65K
FP9-S1-24-1L-QT-5CT	2X4	25W - 50W	3900 - 9360 Lumens	35K - 65K
FP9-S1-24-2L-QT-5CT	2X4	30W - 72W	3750 - 9000 Lumens	35K - 65K

OPTIONS (Ships Installed)

- EM8 - 8W LED Emergency Driver
- EM18 - 18W LED Emergency Driver

ACCESSORIES (Order Separately, Ships on Side)

- FP9-S-MOCS - 12V DC Microwave BiLevel Daylight Indoor AUX Sensor
- FP9-S-OCs - 12V DC PIR BiLevel Daylight Indoor AUX Sensor
- REM6-S - Sensor Remote Control with LCD Display
- FP9-S-SMK14 - 1x4 Surface Mount Kit
- FP9-S-SMK22 - 2x2 Surface Mount Kit
- FP9-S-SMK24 - 2x4 Surface Mount Kit



	W	L	H
1x4	11.9"	47.6"	1.61"
2x2	23.78"	23.78"	1.61"
2x4	23.78"	47.60"	1.61"

LUMEN INFORMATION

Catalog #	Wattage	Lumens	Input Amps (A)	
			120V	277V
FP9-S1-14-1L	15W	1950	0.14	0.06
FP9-S1-14-1L	20W	2600	0.18	0.08
FP9-S1-14-1L	25W	3250	0.23	0.10
FP9-S1-14-1L	30W	3900	0.28	0.12
FP9-S1-14-1L	40W	5200	0.37	0.16
FP9-S1-22-1L	15W	1950	0.14	0.06
FP9-S1-22-1L	20W	2600	0.18	0.08
FP9-S1-22-1L	25W	3250	0.23	0.10
FP9-S1-22-1L	30W	3900	0.28	0.12
FP9-S1-22-1L	40W	5200	0.37	0.16
FP9-S1-24-1L	30W	3900	0.28	0.12
FP9-S1-24-1L	40W	5200	0.28	0.12
FP9-S1-24-1L	50W	6500	0.32	0.14
FP9-S1-24-1L (35K)	60W	7848	0.37	0.16
FP9-S1-24-1L	72W	9360	0.46	0.20