

SPECIFICATIONS

INDOOR

HOUSING

- Aluminum Frame
- Corrosion free powder coat
- Available in 1x4, 2x2, 2x4 sizes
- Housing is only 1" thick
- Mounts directly to 3O or 4O JBOX
- Surface mount bracket included
- White finish

ELECTRICAL

- Quad Tap (QT) - 120-277V
- Dimmable Driver Standard
- Driver is Internal
- Pf > .90
- THD < 20%
- Operating Temperature: -40°C (-40°F) - 45°C (114°F)

OPTICAL SYSTEM

- PS Diffuser
- Beam angle: 110°
- 5CT (field selectable between 27K/30K/35K/40K/50K)
- 50,000 hours @ L₇₀
- CRI > 80

CODE COMPLIANCE

- cULus Listed for Damp Locations
- DLC Listed
- CEC T24 Complaint
- FCC Compliant
- IP44

WARRANTY

- 5 Year



FPS1-EN

LED Color Selectable Surface Mount Edgelit Panel

ORDERING INFORMATION

CATALOG #	Size	Wattage	Lumens	CCT
FPS1-EN-14X1L-QT-5CT	1'x4'	20W/30W/40W	2200/3300/4400 Lm	27K/30K/35K/40K/50K
FPS1-EN-22X1L-QT-5CT	2'x2'	20W/30W/40W	2200/3300/4400 Lm	27K/30K/35K/40K/50K
FPS1-EN-24X1L-QT-5CT	2'x4'	30W/40W/50W	3300/4400/5500 Lm	27K/30K/35K/40K/50K

ACCESSORIES (Ships on Side)

EM25-EN - 25W Emergency Battery Backup

DIMENSIONS

