

SPECIFICATIONS

INDOOR

HOUSING

- Aluminum Frame
- Available in 1x1, 1x2, 1x4, 2x2, 2x4 Size housing
- Housing is only 1" thick
- Mounts directly to 30 or 40 JBOX

ELECTRICAL

- 120V, QT (120-277V)
- Dimmable Driver Standard
- Driver is Internal

OPTICAL SYSTEM

- PMMA LED lenses for optimal light distribution
- 5CT (field selectable between 27K/30K/35K/40K/50K) or MCT (30K/40K/50K)
- 50,000 hours @ L₇₀
- CRI > 80

CODE COMPLIANCE

- cULus Listed for Indoor Locations
- IP20 Rated
- DLC Listed

WARRANTY

- 5 Year



FPS1-EN LED Color Selectable Surface Mount Edgelit Panel

ORDERING INFORMATION

CATALOG #	Description
FPS1-EN-11X18L-120V-5CT	1'x1' Panel, 18W, 1500 Lumens, Selectable (27K-50K), 120V, Triac Dimmable
FPS1-EN-12X22L-120V-5CT	1'x2' Panel, 22W, 2000 Lumens, Selectable (27K-50K), 120V, Triac Dimmable
FPS1-EN-14X40L-QT-MCT	1'x4' Panel, 40W, 4000 Lumens, Selectable (30K/40K/50K), 120-277V, 0-10V Dimmable
FPS1-EN-22X40L-QT-MCT	2'x2' Panel, 40W, 4000 Lumens, Selectable (30K/40K/50K), 120-277V, 0-10V Dimmable
FPS1-EN-24X50L-QT-MCT	2'x4' Panel, 50W, 5000 Lumens, Selectable (30K/40K/50K), 120-277V, 0-10V Dimmable

OPTIONS

- EM - LED Emergency Battery Backup (External 25W)