

SPECIFICATIONS

OUTDOOR

HOUSING

- Sturdy die cast aluminum housing
- Corrosion free powder coat
- Available in white or bronze finishes

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- 0-10V Dimmable driver standard
- Pf > .90
- THD < 15%
- Operating Temperature: -20°C (-4°F) - 50°C (124°F)

OPTICAL SYSTEM

- Clear ribbed Lens
- High quality heat sinks for temperature control
- IC current controlled LED circuits
- Beam angle: 150°
- 50,000 Hours @ L₇₀
- CRI > 80
- Field Selectable Color Temperature (30K/40K/50K)

MOUNTING

- Surface Mount
- 4 1/2" knockouts; 1 on each side for convenient installation
- 3/4" Pendant Mount

CODE COMPLIANCE

- cULus Listed for Wet Locations
- IP65 Rated
- DLC Listed
- JA8 Title24 Approved
- FCC Compliant

WARRANTY

- 5 Year



GL10-EN-MCT

Wattage and Color Tunable LED Canopy

ORDERING INFORMATION

CATALOG #	Wattage	Lumens	Color Temp
GL10-EN-1L-QT-MCT-*	25W/40W/60W	3625/5800/8700 Lm	30K/40K/50K
*Specify Housing: WH -White, BZ -Bronze			

Options (Factory Installed)

- EM** - Emergency Battery Backup
- OCS** - Bi-Level Occupancy Sensor with Daylight Harvesting, external

Accessories (order separately, ships on side)

- HD03R** - Remote for OCS
- HD05R** - Remote for OCS (with screen)

