

SPECIFICATIONS

OUTDOOR

HOUSING

- Heavy duty die cast aluminum housing
- Available in white or bronze finishes

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- 0-10V Dimmable driver standard
- Operating Temperature: -20°C (-4°F) - 50°C (124°F)

OPTICAL SYSTEM

- Polycarbonate lens
- High quality heat sinks for temperature control
- IC current controlled LED circuits
- 50,000 Hours @ L₇₀
- CRI>80
- Field Selectable Color Temperature (30K/40K/50K)

MOUNTING

- Surface Mount
- Pendant mount using 3/4" electrical conduit

CODE COMPLIANCE

- cULus Listed for Wet Locations
- IP65 Rated
- DLC Listed
- JA8 Title24 Approved
- FCC Compliant

WARRANTY

- 5 Year



GL10-EN-MCT

Wattage and Color Tunable LED Canopy

ORDERING INFORMATION

CATALOG #	Wattage	Lumens	Color Temp
GL10-EN-1L-QT-MCT-*	25W/40W/60W	3600/5800/8700 Lm	30K, 40K, 50K

*Specify Housing: **WH-White**, **BZ-Bronze**

Options (Factory Installed)

EM	- Emergency Battery Backup
OCS	- Bi-Level Occupancy Sensor with Daylight Harvesting, external
CC	- Custom Color

Accessories (order separately, ships on side)

REM3-EN	- Remote for OCS
REM4-EN	- Remote for OCS (with screen)

