

SPECIFICATIONS

OUTDOOR

HOUSING

- Heavy duty die cast aluminum housing
- White finish standard, black and dark bronze also available

ELECTRICAL

- Quad Tap (QT) - 120 - 277V
- 0-10V Dimmable driver standard (10-100%)
- Operating Temperature: -40°C (-40°F) - 45°C (113°F)
- THD < 20%
- Power Factor > 90%

OPTICAL SYSTEM

- Polycarbonate lens
- High quality heat sinks for temperature control
- IC current controlled LED circuits
- 50,000 Hours @ L₇₀
- CRI ≥ 80
- MCT: Switchable between 4000K and 5000K

MOUNTING

- Mounting Bracket suitable for JBox mounting
- Supports pendant mounting

CODE COMPLIANCE

- cULus Listed for Wet Locations
- DLC Listed

WARRANTY

- 5 Year



GL9-MS-MCT LED Selectable Canopy

ORDERING INFORMATION

CATALOG #	Wattage	Lumens	CCT
GL9-MS-1L-QT-MCT	22W/34W/46W/60W	3600 / 5000 / 6500 / 7700 Lms	40K/50K

OPTIONS (Factory Installed)

OCS	- Occupancy Sensor
EM	- Battery Backup (900 lumens)
BK	- Black Housing
BZ	- Dark Bronze Housing

