

SPECIFICATIONS

HIGHBAYS

HOUSING

- 22 Gauge painted steel
- Access plate in back for easy wiring
- Ideally mounted for 15-40' ceilings

ELECTRICAL

- Quad Tap (QT) - 120-277V
- 0-10V Dimmable driver standard
- 480V Transformer available
- Max Operating Temperature: 45°C (113°F)

OPTICAL SYSTEM

- White reflector
- Clear and frosted lenses available
- Color temps offered in 30K - 50K
- 100,000 Hours @ L₇₀
- CRI > 80

MOUNTING

- Cable mounting kits available
- Mounting minimum 18" from ceiling

CODE COMPLIANCE

- cETLus Listed for Indoor Locations
- ARRA Compliant

WARRANTY

- 5 Year



HB22-LED LED Highbay

ORDERING INFORMATION

MODEL#	Length x Wattage	Driver	CCT	Lens
HBLED22	24"	QT	30K	Blank (no lens)
	24X80L (10,000 Lm)		35K	FL (Frosted Lens)
	24X122L (15,000 Lm)		40K	CL (Clear Lens)
	24X175L (21,525 Lm)		50K	
	48"			
	48X80L (10,000 Lm)			
	48X122L (15,000 Lm)			
	48X149L (25,150 Lm)			
	48X175L (25,050 Lm)			
	48X186L (26,350 Lm)			
	48X215L (31,380 Lm)			
	48X220L (33,000 Lm)			
	48X260L (36,780 Lm)			
	48X273L (38,230 Lm)			
	48X280L (41,120 Lm)			
	48X315L (45,440 Lm)			
	48X355L (50,110 Lm)			
	48X400L (60,000 Lm)			

Options / Accessories on 2nd Page


OPTIONS

OPTIONS (Factory Installed)

Light	
UPD	- 45W Uplight, 5500 Lm (downlight only standard)
Sensor	
OCS	- Occupancy Sensor
OCSDH	- OCS with Dimming and Daylight Harvesting
Battery Backup	
EM14	- 14W Battery Backup
Wireguard	
WG	- Wraparound Wireguard
Cords	
CS8	- 8' Cordset
CS12	- 12' Cordset
WP	- 6' 3-Wire MC whip
WP12	- 12' 3-Wire MC whip

ACCESSORIES (Order Separately)

GK10-M	- 10' Cable Mounting Kit
GK15-M	- 15' Cable Mounting Kit
HBLED22-2-WG	- 2' Wireguard
HBLED22-4-WG	- 4' Wiregaurd



DIMENSIONS

