

SPECIFICATIONS

HIGHBAYS

HOUSING

- One-piece fiberglass housing
- Poured, closed-cell gasket
- Rugged, corrosion-resistant
- 5VA flammability rating
- Neoprene gasket
- Interior die formed steel tray
- Stainless steel latches and mounting brackets
- External hanging bracket

CODE COMPLIANCE

- cULus Listed for Damp Locations
- FCC Compliant
- RoHS Compliant
- NSF
- NEMA 4X

WARRANTY

- 5 year warranty

ELECTRICAL

- High efficiency LED board
- Thermally protected electronic QT (120-277V) ballast
- 0-10V Dimming
- 4kV Surge Protection
- 50,000 hours @ L₇₀

OPTICAL SYSTEM

- Injection molded diffuser
- Impact resistant acrylic, frosted lens and UV stabilized polycarbonate available
- Available in 3000K, 3500K, 4000K and 5000K color temperatures
- Power factor <.90
- CRI > 80
- THD < 20%



HB9-K-LED LED Vapor Proof Highbay

CATALOG#	Size/Wattage/Lumens	Driver	Color
HB9-K	2X17L (2ft, 17W, 3166 Lumens)	QT (120-277V)	30K
	2X24L (2ft, 24W, 4350 Lumens)		35K
	2X31L (2ft, 31W, 5470 Lumens)		40K
	2X39L (2ft, 39W, 6452 Lumens)		50K
	4X17L (4ft, 17W, 3220 Lumens)		
	4X24L (4ft, 24W, 4480 Lumens)		
	4X30L (4ft, 30W, 5705 Lumens)		
	4X37L (4ft, 37W, 6910 Lumens)		
	4X51L (4ft, 51W, 9660 Lumens)		
	4X72L (4ft, 72W, 13,440 Lumens)		
	4X96L (4ft, 96W, 17,280 Lumens)		
	4X105L (4ft, 105W, 18,900 Lumens)		
	4X111L (4ft, 111W, 20,730 Lumens)		
	4X144L (4ft, 144W, 25,920 Lumens)		
	4X210L (4ft, 210W, 35,391 Lumens)		
	4X216L (4ft, 216W, 41,712 Lumens)		

OPTIONS (Factory Installed)

- EM5 - 5W Emergency Battery
- EM10 - 10W Emergency Battery
- EM14 - 14W Emergency Battery
- OCS - Occupancy Sensor
- PCL - Polycarbonate Lens
- SSL - Stainless Steel Latches

ACCESSORIES (Order Separately)

- SSMB-K - Stainless Steel Mounting Bracket

