

SPECIFICATIONS

HIGHBAYS

HOUSING

- 22 Gauge painted steel
- Enhanced white reflector
- Available in 2' and 4'

ELECTRICAL

- Quad Tap (QT) - 120-277VAC
- 0-10V dimmable driver standard

OPTICAL SYSTEM

- Clear and Frosted Lenses available
- Available in 3000K, 35000K, 4000K, and 5000K
- Power Factor > .90
- THD <20%
- CRI > 80

MOUNTING

- Can be surface, pendant, stem, or chain mounted

CODE COMPLIANCE

- cETLus Listed
- Meets UL Requirements
- ARRA Compliant
- Meets DLC Requirements

WARRANTY

- 5 Year warranty
- 10 Year Available



HBLED22 LED Full Body Highbay

ORDERING INFORMATION

CATALOG #	Size	Wattage	Lumens
HBLED22-2X80L-QT-*	2'	80W	10,000 Lumens
HBLED22-2X122L-QT-*	2'	122W	15,000 Lumens
HBLED22-2X175L-QT-*	2'	175W	21,525 Lumens
HBLED22-4X80L-QT-*	4'	80W	10,000 Lumens
HBLED22-4X122L-QT-*	4'	122W	15,000 Lumens
HBLED22-4X149L-QT-*	4'	149W	21,150 Lumens
HBLED22-4X175L-QT-*	4'	175W	25,050 Lumens
HBLED22-4X186L-QT-*	4'	186W	26,350 Lumens
HBLED22-4X215L-QT-*	4'	215W	31,380 Lumens
HBLED22-4X220L-QT-*	4'	220W	33,000 Lumens
HBLED22-4X260L-QT-*	4'	260W	36,780 Lumens
HBLED22-4X273L-QT-*	4'	273W	38,230 Lumens
HBLED22-4X280L-QT-*	4'	280W	41,120 Lumens
HBLED22-4X315L-QT-*	4'	315W	45,440 Lumens
HBLED22-4X355L-QT-*	4'	355W	50,110 Lumens

*Specify 30K, 35K, 40K, 50K

OPTIONS (Factory Installed)

FL	-	Frosted Lens (no lens provided standard)
CL	-	Clear Lens (no lens provided standard)
UP	-	Uplight Only (downlight only is standard)
UPD	-	Up and Down Light (downlight only is standard)
EM10	-	10W Emergency Ballast (1300 Lumens)
OCS	-	Occupancy Sensor
OCD	-	Occupancy Sensor with Daylight Harvesting and Dimming
CS8	-	8' 3-Wire Cordset
CS12	-	12' 3-Wire Cordset
WG	-	Wire Guard
10YR	-	10 Year Warranty

ACCESSORIES (Order Separately, Ships on Side)

HBLED22-WG2	-	2' Wire Guard
HBLED22-WG4	-	4' Wire Guard
GK10	-	10' Air Craft Cable

