

SPECIFICATIONS

HIGHBAYS

HOUSING

- Die cast aluminum housing
- External heat sinks
- White powder coat finish
- Includes 4" stem; maximum stem length of 30'

ELECTRICAL

- Quad Tap (QT) - 120-277VAC
- 0-10V Dimmable Driver standard
- 347-480V Driver optional
- Operating Temperature: -40°C - 50°C (-40°F - 122°F)

OPTICAL SYSTEM

- Available in 5000K
- Offered with clear glass, acrylic, or polycarbonate lenses
- 275 LED Watts; 291W System Watts
- Power Factor > .90
- THD <20%
- CRI > 80
- 299,000 hours @ L₇₀

MOUNTING

- Mount with included 1" die cast hook

CODE COMPLIANCE

- cSAus Listed for Wet Locations
- Meets UL Requirements
- Meets DLC Requirements
- IP65 Rated
- Assembled in USA available

WARRANTY

- 5 Year
- 10 Year Available

ORDERING INFORMATION

CATALOG #	Wattage	Lumens	Color
HBLED32-Q-273L-QT-50K-*	273W	31,135 Lumens	5000K

*Specify Lens: **CL**-Flat Clear, **AC**-Acrylic Conical, **AD**-Acrylic Drop, **PD**-Polycarbonate Drop

OPTIONS (Ships Installed)

480V	- 480V Driver (replaces QT)
OCS	- Microwave Sensor (20' or above - 120-277V only)
SGF	- Single Fusing
DBF	- Double Fusing
EBLED	- Emergency Battery Backup
10YR	- Ten Year Warranty
USA	- Assembled in America

ACCESSORIES (Order Separately, Ships on Side)

HBLED32-Q-WG	- Wire Guard (use with flat lenses)
HBLED32-Q-SC3	- 3' Safety Cable (steel eye and loop ends)



HBLED32-Q
LED Highbay



