

SPECIFICATIONS

HIGHBAYS

HOUSING

- Durable Aluminum Housing
- Available in 2' and 3' models
- Recommended for spaces above 25'

ELECTRICAL

- Quad Tap (QT) - 120-277VAC
- Installed 480V step down transformer available
- 0-10V Dimmable Driver standard
- Power Factor >0.9
- THD <20%
- -4°F - 113°F (-20°C - 45°C)

OPTICAL SYSTEM

- Available in 4000K and 5000K
- Polycarbonate Micro-Filter Lens standard
- CRI >80
- 75,000 @ L₇₀

MOUNTING

- Provided with V-Hooks and Chain Kit standard
- Pendant Mount and Surface Mount brackets optional

CODE COMPLIANCE

- cULus Listed for Indoor Locations
- IP40 Rated
- DLC Premium
- FCC Compliant

WARRANTY

- 5 Year



Shown with optional OCSD

HBLED44-S LED Linear Highbay

ORDERING INFORMATION

CATALOG #	Length x Wattage	Voltage	Color
HBLED44-S	2'	QT (120-277V) 480V	40K
	2X80L (80W, 12,000 Lm)		50K
	2X165L (165W, 24,750 Lm)		
	2X220L (220W, 33,000 Lm)		
	3'		
	3X225L (225W, 33,750 Lm)		

OPTIONS (Ships Installed)

- EM - Installed Emergency Battery Backup (24' max height)
- OCS - PIR On/Off Occupancy Sensor
- OCSD - PIR Bi-Level Dimming Smart Sensor

ACCESSORIES (Ships on the Side)

- HBLED44-PMB - Pendant Mount Bracket
- HBLED-S-RC - Remote for Sensor
- GK10-S - 10' Aircraft Cables

2ft Models

23.62"L x 11.81"W x 1.87"H
5.29lbs

3ft Models

35.10"L x 14.17"W x 1.87"H
8.16lbs

ELECTRICAL INFORMATION

Catalog #	Input Amps (A)	
	120V	277V
HBLED44-S-80L (40K)	0.67	0.29
HBLED44-S-80L (50K)	0.67	0.29
HBLED44-S-165L (40K)	1.38	0.60
HBLED44-S-165L (50K)	0.38	0.60
HBLED44-S-220L (40K)	1.83	0.79
HBLED44-S-220L (50K)	1.83	0.79
HBLED44-S-225L (40K)	1.88	0.81
HBLED44-S-225L (50K)	1.88	0.81