

SPECIFICATIONS

HOUSING

- Copper-free aluminum housing

ELECTRICAL

- Quad Tap (120/208/240/277VAC)
- 480V driver optional
- Dimmable driver optional
- Operating Temperature: -40°F - 130°F (-40°C - 55°C)

OPTICAL SYSTEM

- Offered in 30K - 60K
- Available in multiple optics
- CRI \geq 70

MOUNTING

- Surface mounting and pendant mounting

CODE COMPLIANCE

- Class I, Div II, Groups A, B, C, D
- Class II, Div I, Groups E, F, G
- Class II, Div II, Groups F, G
- Class III
- UL844, UL1598, and UL8750 Listed
- CSA Listed
- IP66 Rated
- Meets DLC Requirements

WARRANTY

- 5 Year



HLFL3-F Hazardous Location Flood Light

CATALOG#	Wattage/Lumens	Voltage	Color	Optic (degrees)
HLFL3-F	20L (2,700 Lumens)	QT	30K	40D
	40L (5,400 Lumens)		40K	60D
	60L (8,100 Lumens)		50K	90D
	80L (10,800 Lumens)		60K	120D
	100L (13,500 Lumens)			
	120L (15,600 Lumens)			
	150L (20,250 Lumens)			
	200L (28,000 Lumens)			
	250L (35,000 Lumens)			
	300L (42,000 Lumens)			
	400L (56,000 Lumens)			


OPTIONS (Factory Installed)

- DIM - Dimmable Driver
- 480V - 200V - 480V
- EBLED - Integral Battery Backup


ACCESSORIES (Order Separately, Ships on Side)

- HLFL3-F-JBOX - Junction Box
- HLFL3-F-CSM - Ceiling/Surface Mount with JBox: 3/4" NPT
- HLFL3-F-WM90 - 90° Wall Mount
- HLFL3-F-WMJB90 - 90° Wall Mount with JBox: 3/4" NPT
- HLFL3-F-WMJB25 - 25° Wall Mount with JBox: 3/4" NPT
- HLFL3-F-PM90 - 90° Pole Mount: 1^{1/2}" NPT
- HLFL3-F-PM25 - 25° Pole Mount: 1^{1/2}" NPT


JBOX




WMJ25




WMJ90




WM90




PM25




PM90




20W / 40W / 60W



80W / 100W



150W / 200W



250W / 300W / 400W

