

SPECIFICATIONS

HAZARDOUS

HOUSING

- Copper-Free Cast Aluminum Housing
- Gray painted finish

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- 347-480V Optional
- 0-10V Dimming Optional
- Operating Temperature: -40°C (-40°F) - 55°C (130°F)

OPTICAL SYSTEM

- Impact resistant clear or ribbed lenses available
- IC current controlled LED circuits
- CRI > 74
- 4000K or 5000K

MOUNTING

- Surface Mounting standard with bracket
- Multiple mounting options available

CODE COMPLIANCE

- UL Listed for Wet Locations
- CSA Listed
- Class I, Div II, Groups A, B, C, & D
- Class II, Div II, Groups F & G
- Class III
- IP66 Rated
- DLC Listed

WARRANTY

- 5 Year Warranty
- 10 Year Warranty optional



HLLB1-F LED Hazardous Location LowBay

CATALOG #	Wattage	Size	Lumens	Lens
HLLB1-F-20L-QT-*#-^		20W	2,600 Lumens	
HLLB1-F-40L-QT-*#-^		40W	5,200 Lumens	
HLLB1-F-60L-QT-*#-^		60W	7,800 Lumens	
HLLB1-F-80L-QT-*#-^		80W	10,400 Lumens	
HLLB1-F-100L-QT-*#-^		100W	13,000 Lumens	
HLLB1-F-120L-QT-*#-^		120W	15,600 Lumens	
HLLB1-F-150L-QT-*#-^		150W	19,500 Lumens	
HLLB1-F-200L-QT-*#-^		200W	26,000 Lumens	

*Specify Color Temp: **40K**; **50K**

#Specify Optics (Degrees): **40D**; **60D**; **90D**; **100D**; **110D**; **120D**

^Specify Hazardous Rating: **C1D2**; **C2D2**; **C3**

EX: HLLB1-F-60L-QT-50K-90D-C2D2

OPTIONS (Factory Installed)

480V	-	347-480V Driver
DIM	-	0-10V Dimming
10YR	-	10 Year Warranty

ACCESSORIES (Order Separately, Ships on Side)

HLLB1-F-FGG	-	Frosted Glass Globe and Guard
HLLB1-F-DREFL	-	Dome Reflector (used with FGG)
HLLB1-F-AREFL	-	Angled Reflector (used with FGG)
HLLB1-F-PSM	-	Pole Stanchion Mount
HLLB1-F-PSM25	-	25° Pole Stanchion Mount
HLLB1-F-ARM	-	Arm Mount Bracket
HLLB1-F-CMB	-	Ceiling Mount Bracket
HLLB1-F-PM	-	Pendant Mount
HLLB1-F-PM12	-	12° Pendant Mount
HLLB1-F-JBOX	-	JBox

Mounting Options

