VersaLED Lighting
Versatile Lighting Solutions

Project

Type

Catalog Number

SPECIFICATIONS — HAZARDOUS

HOUSING
- Heavy duty die cast aluminum housing
- Available in 2' and 4' models
- Powder coated finish
- Corrosion resistant housing and hardware

ELECTRICAL
- Quad Tap (QT) - 120-277V
- 480V available
- Dimmable driver available

OPTICAL SYSTEM
- Opal polycarbonate lens standard, clear glass lens optional
- Available in 4000K and 5000K
- CRI ≥ 70
- 85,000 Hours L_{70}
- Operating Temperature: -40°C - 60°C (-40°F - 140°F)

MOUNTING
- Surface and Pendant mounting standard
- Additional accessories available

CODE COMPLIANCE
- cETLus Listed
- Class I, Division II, Groups A, B, C, D
- Class II, Division I, Groups E, F, G
- Class II, Division II, Groups F, G
- Class III
- ABS
- IP66 Rated
- RoHS Compliant
- Meets UL Requirements

WARRANTY
- 5 year warranty
- 10 year warranty optional





HLTN-F
LED Hazardous Location Fixture

CATALOG #	Wattage	Length	Lumens
HLTN-F-2X20L-QT-*	20W	2ft.	2,000 - 2,800
HLTN-F-2X40L-QT-*	40W	2ft.	4,800 - 5,600
HLTN-F-4X40L-QT-*	40W	4ft.	4,800 - 5,600
HLTN-F-4X60L-QT-*	60W	4ft.	7,200 - 8,400
HLTN-F-4X80L-QT-*	80W	4ft.	10,000 - 11,200

Specify Color Temp: 30K, 40K, 50K, 60K

OPTIONS (Ships Installed)		
DIM	-	Dimmable Driver
480V	-	277V - 480V
EBLED	-	Integral Battery Backup
OCS	-	Occupancy Sensor
GL	-	Glass Lens
BAA*	-	Buy American Compliant
TAA*	-	Trade Agreements Act Compliant

**Contact factory for availability*

ACCESSORIES (Order separately, ships on side)		
HLTN-F-JBOX	-	Junction Box
HTN-F-FL	-	Flat Lens