

## SPECIFICATIONS

HAZARDOUS

### HOUSING

- Copper-free aluminum housing
- Typically used in smaller spaces with mounting heights from 6-12'

### ELECTRICAL

- Quad Tap (120-277V)
- Dimmable Driver Optional
- Operating Temp: -40°F - 149°F (-40°C - 65°C)
- 10kV surge protection

### OPTICAL SYSTEM

- Tempered glass lens
- Opal globe optional
- Offered in 30K - 60K
- 120o standard; contact for additional optics
- CRI: 80

### MOUNTING

- Supplied standard with pendant mount and strut mounting clips
- Wall mount, stanchion, and surface mounting available

### CODE COMPLIANCE

- Class I, Div I, Groups C, D
- Class I, Div II, Groups A, B, C, D
- Class II, Div II, Groups F, G
- Class III
- cETLus Listed for Wet Locations
- UL844, UL1598, and UL8750 Listed
- CSA Listed
- IP66 Rated
- ROHS Compliant
- FCC Compliant

### WARRANTY

- 5 Year

### ORDERING INFORMATION

CATALOG#	Illumination	Voltage	Color
HLVP3-F	10L (1,400 Lumens)	QT	30K
	20L (2,800 Lumens)		40K
	30L (4,200 Lumens)		50K
	40L (5,600 Lumens)		60K

### OPTIONS (Factory Installed)

DIM	- Dimmable Driver
CG	- Clear Globe
CGWG	- Clear Globe and Wire Guard
FG	- Frosted Globe
FGWG	- Frosted Globe and Wire Guard
DRFL	- Dome Reflector
ARFL	- Angled Reflector
OCS	- Sensor
BAA	- BAA Compliant
TAA	- Trade Agreements Act Compliant

### ACCESSORIES (Order Separately, Ships on Side)

HLVP3-F-JBOX	- Junction Box
HLVP3-F-CSM	- Ceiling/Surface Mount with JBox: 3/4" NPT
HLVP3-F-WM90	- 90° Wall Mount
HLVP3-F-WMJB90	- 90° Wall Mount with JBox: 3/4" NPT
HLVP3-F-WMJB25	- 25° Wall Mount with JBox: 3/4" NPT
HLVP3-F-PM90	- 90° Pole Mount: 1 1/2" NPT
HLVP3-F-PM25	- 25° Pole Mount: 1 1/2" NPT



## HLVP3-F Hazardous Location Jelly Jar

