

SPECIFICATIONS

HAZARDOUS

HOUSING

- Copper-free aluminum housing
- Dimensions: 6.8" x 16.8" x 16.1"

ELECTRICAL

- Quad Tap (120/208/240/277VAC)
- 480V Driver
- Dimmable driver optional
- Operating Temperature: -40°F - 149°F (-40°C - 65°C)

OPTICAL SYSTEM

- Offered in 40K, 50K, 60K
- Available in multiple optics
- 150,000 hours @ L₇₀
- CRI≥70

MOUNTING

- Multiple mounting accessories available

CODE COMPLIANCE

- Class I, Div I, Groups C, D
- Class I, Div II, Groups A, B, C, D
- Class II, Div II, Groups F, G
- Class III
- UL844, UL1598, and UL8750 Listed
- CSA Listed
- IP66 Rated
- Meets DLC Requirements

WARRANTY

- 5 Year

ORDERING INFORMATION

CATALOG#	Wattage/Lumens	Voltage	Color	Rating	Optic (degrees)
HLVP4-F	40L (5,400 Lumens)	QT	40K	C1D1	40D
	60L (8,100 Lumens)		50K	C1D2	60D
	80L (10,800 Lumens)		60K	C2D1	90D
				C3	100D
					110D
					120D

OPTIONS (Factory Installed)

DIM	- Dimmable Driver
480V	- 277V - 480V
EBLED	- Integral Battery Backup
LG	- Less Globe/Guard

ACCESSORIES (Order Separately, Ships on Side)

HLVP4-F-DRFL	- Dome Reflector
HLVP4-F-ARFL	- Angled Reflector
HLVP4-F-STM	- Stanchion Mount
HLVP4-F-STM25	- 25° Stanchion Mount
HLVP4-F-WAM	- Wall Arm Mount
HLVP4-F-CM	- Ceiling Mount
HLVP4-F-PDM	- Pendant Mount
HLVP4-F-PDM12	- 12° Pendant Mount
VLVP4-F-JBOX	- Hazardous Junction Box



HLVP4-F Hazardous Location Jelly Jar