

SPECIFICATIONS

HAZARDOUS

HOUSING

- Copper-free aluminum housing
- Polyester powdercoat finish

ELECTRIC

- Quad Tap 120-277VAC
- Dimmable Driver Optional
- Operating Temp: -4°F - 140°F (-20°C - 60°C)
- 10kV surge protection

OPTICAL SYSTEM

- Tempered glass lens
- Frosted globe optional
- Offered in 3000K - 5000K
- CRI: 70

MOUNTING

- Pendant mount, ceiling mount, surface/wall mount
- Wall mount, stanchion, and surface mounting available

CODE COMPLIANCE

- Class I, Div II, Groups A, B, C, D
- Class II, Div I, Groups E, F, G
- Class II, Div II, Groups F, G
- Class III
- cSAus Listed for Wet Locations
- UL924, UL1598AListed
- IP66 Rated
- NEMA 4X

WARRANTY

- 5 Year
- 10 year optional



HLVP5-F Hazardous Location Jelly Jar

ORDERING INFORMATION

CATALOG#	Illumination	Voltage	Color
HLVP5-F	10L (1,400 Lumens)	QT	30K
	20L (2,800 Lumens)		40K
	30L (4,200 Lumens)		50K

OPTIONS (Factory Installed)

DIM	- 0-10V Dimmable Driver
FL	- Flat Glass Lens
WG	- Wire Guard
CG	- Clear Globe
CGWG	- Clear Globe and Wire Guard
FG	- Frosted Globe
FGWG	- Frosted Globe and Wire Guard
EM	- Emergency Battery Backup (with integrated junction box for driver)
DRFL	- Dome Reflector
ARFL	- Angled Reflector
BAA	- Buy American Act Compliance
TAA	- Trade Agreements Acts Compliant
10YR	- 10 Year Warranty

ACCESSORIES (Order Separately, Ships on Side)

HLVP5-F-PA	- Pendant
HLVP5-F-JBOX	- Junction Box
HLVP5-F-WM90	- 90° Wall Mount
HLVP5-F-CSM	- Ceiling / Surface Mounting



