

SPECIFICATIONS

INDOOR

HOUSING

- Housing is die formed cold rolled steel
- High reflectance baked white enamel finish
- End plate doubles as coupler for continuous row mounting
- 7/8" Knockouts provided for flexible conduit attachment
- Offered in 2', 4', and 8'

ELECTRICAL

- Quad Tap (QT) - 120-277V
- Dimmable driver standard
- $Pf \geq .90$
- $THD \leq 20\%$
- 4kV Surge protection
- 50,000 hours @ L_{70}

OPTICAL SYSTEM

- White Steel reflectors standard
- CRI >80
- Offered in 30K, 35K, 40K, 50K

MOUNTING

- Can be surface or pendant mounted

CODE COMPLIANCE

- cULus Listed for Damp Locations
- FCC Compliant
- RoHS Compliant
- BAA Compliant

WARRANTY

- 5 Year



ORDERING INFORMATION

MODEL#	Size x Wattage	Driver	Color
IND-K	<u>2ft.</u>	QT	30K
	2X17L (17W, 3166 Lm)		35K
	2X24L (24W, 4350 Lm)		40K
	2X31L (31W, 5470 Lm)		50K
	2X39L (39W, 6452 Lm)		
	<u>4 ft.</u>		
	4X17L (17W, 3220 Lm)		
	4X24L (24W, 4480 Lm)		
	4X30L (30W, 5705 Lm)		
	4X37L (37W, 6910 Lm)		
	4X48L (48W, 8640 Lm)		
	4X70L (70W, 11,797 Lm)		
	<u>8 ft.</u>		
	8X17L (17W, 3220 Lm)		
	8X24L (24W, 4480 Lm)		
	8X30L (30W, 5705 Lm)		
	8X37L (37W, 6910 Lm)		
	8X48L (48W, 8640 Lm)		
	8X70L (70W, 11,797 Lm)		
	8X74L (74W, 13,820 Lm)		
	8X96L (96W, 17,280 Lm)		
	8X140L (140W, 23,594Lm)		

OPTIONS (Factory Installed)

SV	- Silver Reflector (White Standard)
BK	- Black Reflector (White Standard)
EM5	- 5W Emergency Battery
EM10	- 10W Emergency Battery
EM14	- 14W Emergency Battery
OCS	- External Occupancy Sensor
OCS D	- Bi-Level Dimming System
GO	- Grounded Outlet
TS	- Toggle Switch
PC	- Pull Chain Switch
CP	- Cord and Plug

ACCESSORIES (Order Separately, Ships on Side)

IND-WG4	- Wire Guard (order two for 8' housing)
GK10-K	- 10' Air Craft Cable
GK15-K	- 15' Air Craft Cable

IND-K-LED LED Industrial Light

