

SPECIFICATIONS

INDOOR

HOUSING

- Housing is die formed cold rolled steel
- High reflectance baked white enamel finish
- End plate doubles as coupler for continuous row mounting
- Knockouts provided for flexible conduit attachment
- Offered in 2', 4', and 8'

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- Dimmable driver standard

OPTICAL SYSTEM

- White Steel reflectors available
- CRI >80
- Offered in 30K, 35K, 40K, 50K

MOUNTING

- Can be surface, stem, or chain mounted

CODE COMPLIANCE

- cETLus Listed for Damp Locations
- Meets UL Requirements
- ARRA Compliant

WARRANTY

- 5 Year



IND-K-LED LED Industrial Light

MODEL#	Size x Wattage	Driver	Color
IND-K	2ft.	QT	30K
	2X17L (17W, 3166 Lm)		35K
	2X24L (24W, 4350 Lm)		40K
	2X31L (31W, 5470 Lm)		50K
	2X39L (39W, 6452 Lm)		50K
	4 ft.		
	4X17L (17W, 3220 Lm)		
	4X24L (24W, 4480 Lm)		
	4X30L (30W, 5705 Lm)		
	4X37L (37W, 6910 Lm)		
	4X48L (48W, 8640 Lm)		
	4X70L (70W, 11,797 Lm)		
	8 ft.		
	8X17L (17W, 3220 Lm)		
	8X24L (24W, 4480 Lm)		
	8X30L (30W, 5705 Lm)		
	8X37L (37W, 6910 Lm)		
	8X48L (48W, 8640 Lm)		
	8X70L (70W, 11,797 Lm)		
	8X74L (74W, 13,820 Lm)		
	8X96L (96W, 17,280 Lm)		
	8X140L (140W, 23,594Lm)		

OPTIONS (Factory Installed)

EM10	- 10W Emergency Battery
CP6	- Cord and Plug
OCSE	- External Occupancy Sensor
OCSI	- Internal Occupancy Sensor
PC	- Pull Chain Switch
TGS	- Toggle Switch
REFLS	- Symmetric White Steel Reflector
REFLA	- Asymmetric White Steel Reflector
FL	- Frosted Lens over LED Boards

ACCESSORIES (Order Separately, Ships on Side)

IND-WG4	- Wire Guard (order two for 8' housing)
CK2-M	- (2) 2' Chains with V-Hooks

