

SPECIFICATIONS

OUTDOOR

HOUSING

- Die cast aluminum housing
- Powdercoat black or verde green housing available
- Corrosion resistant housing and hardware
- OxyShield multi-stage anti-oxidation process
- Silicone rubber gasket

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- Operating Temperature: -20°C (-4°F) - 40°C (104°F)

OPTICAL SYSTEM

- Polycarbonate Lens
- IC current controlled LED circuits
- Available in 4000K
- 30° and 60° Beams offered

MOUNTING

- Threaded pipe (NPS 1/2") which attaches to a junction box is standard
- Ground stake optional for ground mounting

WARRANTY

- 5 Year



LD2-DM LED Landscape Flood

ORDERING INFORMATION

MODEL#	Wattage	Lumens	Color	Beam Spread
LD2-DM-15L-QT-40K-30D-*	15W	1,650	4000K	30°
LD2-DM-15L-QT-40K-60D-*	15W	1,650	4000K	60°
LD2-DM-28L-QT-40K-30D-*	28W	3,000	4000K	30°
LD2-DM-28L-QT-40K-60D-*	28W	3,000	4000K	60°

*Specify Color: **BL**-Black; **GR**-Verde Green

ACCESSORIES (Order Separately, Ships on Side)

LD2-DM-STK - Ground Stake

