

## SPECIFICATIONS

OUTDOOR

### HOUSING

- Die cast aluminum housing
- Powdercoat bronze finish standard
- Corrosion resistant housing and hardware
- OxyShield multi-stage anti-oxidation process
- Silicone rubber gasket

### ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- 0-10V Dimming
- Operating Temperature: -40°C (-40°F) - 40°C (104°F)

### OPTICAL SYSTEM

- Tempered Lens
- IC current controlled LED circuits
- Available in 30K and 50K

### MOUNTING

- Threaded pipe (NPS 1/2") which attaches to a junction box is standard
- Ground stake optional for ground mounting

### CODE COMPLIANCE

- IP65
- UL Listed for Wet Location

### WARRANTY

- 5 Year



## LD2-W LED Landscape Flood

## ORDERING INFORMATION

MODEL#	Wattage	Lumens	Color
LD2-W-15L-QT-30K	15W	1,530	3000K
LD2-W-15L-QT-50K	15W	1,650	5000K
LD2-W-28L-QT-30K	28W	3,000	3000K
LD2-W-28L-QT-50K	28W	2,760	5000K
LD2-W-42L-QT-30K	42W	4,500	3000K
LD2-W-42L-QT-50K	42W	4,200	5000K

### ACCESSORIES (Order Separately, Ships on Side)

LD2-W-SH - Shroud

