

SPECIFICATIONS

OUTDOOR

HOUSING

- Die cast aluminum housing
- Powdercoat bronze finish standard
- Corrosion resistant housing and hardware
- OxyShield multi-stage anti-oxidation process
- Silicone rubber gasket

ELECTRICAL

- Quad Tap (QT) - 120/208/240/277V
- 0-10V Dimming
- Operating Temperature: -40°C (-40°F) - 40°C (104°F)
- Power factor >.90
- 70,000 hours @ L₇₀

OPTICAL SYSTEM

- Plaid Tempered Lens
- Aluminum reflectors
- IC current controlled LED circuits
- Available in 30K and 50K
- Beam angle: 35°
- CRI ≥ 80

MOUNTING

- 1/2" Threaded knuckle stem
- Knuckle mount

CODE COMPLIANCE

- IP65
- UL Listed for Wet Location

WARRANTY

- 5 Year



LD2-W
LED Landscape Flood

ORDERING INFORMATION

MODEL#	Wattage	Driver	CCT	Mount
LD2-W	15L (15W, 1900 Lms)	QT	30K	KN (Knuckle Mount)
	28L (28W, 2800 Lms)		50K	
	42L (42W, 4200 Lms)			

ACCESSORIES (Order Separately, Ships on Side)

LD2-W-SH - Shroud

