

SPECIFICATIONS

INDOOR

HOUSING

- Die Formed 22-gauge steel housing
- White housing standard
- Fixture can be surface or pendant mounted
- Knockouts on ends allow for continuous wireway mounting
- Housings offered in 2', 4', and 8'
- 8' fixtures have steel mullion to join two individual diffusers

ELECTRICAL

- Quad Tap (QT) - 120-277V
- 0-10V Dimmable Driver Standard
- Pf > .90
- THD < 20%
- 4kV Surge Protection
- 50,000 hours @ L₇₀

OPTICAL SYSTEM

- 3000K - 5000K
- CRI ≥ 80

CODE COMPLIANCE

- cULus Listed for Damp Locations
- FCC Compliant
- RoHS Compliant
- BAA Compliant

WARRANTY

- 5 Year



LID2-K 2"X 2" LED Pendant/Wall Light

ORDERING INFORMATION

MODEL#	Mount	Length x Wattage	Driver	CCT
LID2-K	PM (Pendant Mount)	<u>2' Down</u>	QT	30K
	WM (Wall Mount)	2X17L (17W, 3166 Lm)		35K
		2X24L (24W, 4350 Lm)		40K
		2X31L (31W, 5470 Lm)		50K
		2X39L (39W, 6452 Lm)		
		<u>4' Down</u>		
		4X17L (17W, 3220 Lm)		
		4X24L (24W, 4480 Lm)		
		4X30L (30W, 5705 Lm)		
		4X37L (37W, 6910 Lm)		
		4X48L (48W, 8640 Lm)		
		4X70L (70W, 11,797 Lm)		
		<u>8' Down</u>		
		8X30L (30W, 5705 Lm)		
		8X37L (37W, 6910 Lm)		
		8X48L (48W, 8640 Lm)		
		8X78L (78W, 13,820 Lm)		
		8X99L (99W, 17,280 Lm)		
		8X128L (128W, 22,008 Lm)		

OPTIONS (Factory Installed)

UDL	- Up/Down Light (Down Light standard)
EM5	- 5W Emergency Battery
EM12	- 12W Emergency Battery

ACCESSORIES (Factory Installed)

LID-K-JR90	- 90° Joiner Bracket- Allows for Square/Rectangle Configuration
------------	---

