

SPECIFICATIONS

INDOOR

HOUSING

- Die Formed 22-gauge steel housing
- White housing standard
- Can be installed individually or in a continuous run
- Fixture can be ceiling surface mounted or pendant hung by stem or cable
- Knockouts on ends allow for continuous wireway mounting
- Housings offered in 2', 4', and 8'
- 4' and 8' fixtures have steel mullion to join two individual diffusers

ELECTRICAL

- Quad Tap (QT) - 120-277V
- 120V
- Triac Dimmable

OPTICAL SYSTEM


- Snap in lens
- Direct/Indirect light
- 3000K - 5000K
- CRI $\geq$ 80

CODE COMPLIANCE

- cULus Listed for Damp Locations
- BAA Compliant

WARRANTY

- 5 Year



LID4-K 2"X 3" LED Pendant/Wall Light

ORDERING INFORMATION

MODEL#	Mount	Length x Wattage	Driver	CCT	Direction
LID4-K	PM (Pendant Mount)	<u>2' Down</u>	QT	30K	UDL (Up/Down Light)
	WM (Wall Mount)	2X17L (17W, 3166 Lm)		35K	
		2X24L (24W, 4350 Lm)		40K	
		2X31L (31W, 5470 Lm)		50K	
		2X39L (39W, 6452 Lm)			
		<u>4' Down</u>			
		4X17L (17W, 3220 Lm)			
		4X24L (24W, 4480 Lm)			
		4X30L (30W, 5705 Lm)			
		4X37L (37W, 6910 Lm)			
		4X48L (48W, 8640 Lm)			
		4X70L (70W, 11,797 Lm)			
		<u>8' Down</u>			
		8X30L (30W, 5705 Lm)			
		8X37L (37W, 6910 Lm)			
		8X48L (48W, 8640 Lm)			
		8X78L (78W, 13,820 Lm)			
		8X99L (99W, 17,280 Lm)			
		8X128L (128W, 22,008 Lm)			

OPTIONS (Factory Installed)

- EM5 - 5W Emergency Battery
- EM10 - 10W Emergency Battery

ACCESSORIES (Factory Installed)

- LID-K-JR90 - 90° Joiner Bracket- Allows for Square/Rectangle Configuration

DIMENSIONS

