

SPECIFICATIONS

INDOOR

HOUSING

- Plastic Housing
- Corncob
- White finish
- Dimensions:
 - 1L: 3.66" H x 3.66" W x 9.8" L
 - 2L: 3.66" H x 3.66" W x 10.98" L
 - 3L: 3.66" H x 3.66" W x 10.98" L
 - 4L: 3.66" H x 3.66" W x 11.57" L
 - 5L: 5.51" H x 5.51" W x 11.61" L
 - 6L: 5.51" H x 5.51" W x 12.20" L
 - 7L: 5.51" H x 5.51" W x 12.99" L

ELECTRICAL

- Quad-Tap (100-277Vac)
- E39 base
- Operating Temperature: -40°C - 60°C (-40°F - 140°F)
- Beam angle: 300°
- 50,000 hours @ L₇₀
- Power Factor > 0.9
- THD < 20%
- 4kV Surge Protection

ILLUMINATION

- Wattage/Lumen selectable
- Plastic Lens
- 180° Beam Angle
- CRI > 80
- MCT: Selectable between 3000K/4000K/5000K

CODE COMPLIANCE

- cULus Listed for Damp Locations
- DLC Listed
- FCC Compliant
- RoHS Compliant

WARRANTY

- 5 Year Warranty



LLP4-SA
Selectable LED Lamp

ORDERING INFORMATION

CATALOG#	Wattage	Lumens	CCT
LLP4-SA-1L-QT-MCT-E39	18W/27W/36W	2520 / 3780 / 5040 Lms	30K/40K/50K
LLP4-SA-2L-QT-MCT-E39	27W/36W/45W	3780 / 5040 / 6300 Lms	30K/40K/50K
LLP4-SA-3L-QT-MCT-E39	36W/45W/54W	5040 / 6300 / 7560 Lms	30K/40K/50K
LLP4-SA-4L-QT-MCT-E39	45W/54W/63W	6300 / 7560 / 8820 Lms	30K/40K/50K
LLP4-SA-5L-QT-MCT-E39	54W/63W/80W	7560 / 8820 / 11,200 Lms	30K/40K/50K
LLP4-SA-6L-QT-MCT-E39	63W/80W/100W	8820 / 11,200 / 14,000 Lms	30K/40K/50K
LLP4-SA-7L-QT-MCT-E39	80W/100W/120W	11,200 / 14,000 / 16,800 Lms	30K/40K/50K