

SPECIFICATIONS

INDOOR

HOUSING

- Easily updates 2x2 and 2x4 fluorescent fixtures to LED

ELECTRICAL

- Quad Tap (QT) - 120-277V
- Dimming Compatible
- Operating Temperature: -4°F (-20°C) - 113°F (45°C)

OPTICAL SYSTEM

- Available with no lens, clear, or frosted polycarbonate lenses
- Available in 40K - 50K
- 50,000 Hours @ L₇₀
- CRI > 80
- THD < 15%

CODE COMPLIANCE

- ETL Listed for Indoor Locations
- IP20 Rated
- DLC Premium

WARRANTY

- 5 Year



MGRK3-EL LED Magnetic Retrofit Kit

ORDERING INFORMATION

MODEL#	Size	Strips	Wattage	Lumens
MGRK3-EL-22X20L-QT-*#	2X2	1	20W	2500 - 2700
MGRK3-EL-22X30L-QT-*#	2X2	2	30W	3750 - 4050
MGRK3-EL-22X40L-QT-*#	2X2	3	40W	5000 - 5400
MGRK3-EL-24X24L-QT-*#	2X4	1	24W	3120 - 3216
MGRK3-EL-24X30L-QT-*#	2X4	2	30W	4050 - 4170
MGRK3-EL-24X40L-QT-*#	2X4	2	40W	5200 - 5360
MGRK3-EL-24X45L-QT-*#	2X4	3	45W	6075 - 6255
MGRK3-EL-24X60AL-QT-*#	2X4	3	60W	7800 - 8040
MGRK3-EL-24X60BL-QT-*#	2X4	4	60W	7800 - 8100
MGRK3-EL-24X80L-QT-*#	2X4	4	80W	10160 - 10560

*Specify CCT: 40K, 45K, 50K

#Specify Lens: FL-Frosted, CL-Clear, NL-No Lens

