

Project

Type

Catalog Number

MULTI-FAMILY

SPECIFICATIONS

- Rectangular front-lighted LED mirror (backlit projection lighting)

- 44" W x 32" H (mounts only one way, W X H)
- 5mm polished glass, copper free
- Anodized aluminum frame, SS screws
- Switch provided

DIMENSIONS

MATERIAL

- Frame Depth: 1.50"
- Frame Perimeter: 1.0" inside of mirror perimeter
- Inner frame perimeter approx 5.75" inside mirror perimeter
- Top mounting bar: 7.50" from top edge
- Frosted area 2"
- Mirrored area outside of frosted glass 2" wide

MOUNTING

- Frame has 4-5 integrated aluminum mounting brackets attached to the frame used to secure the frame to the wall.
- 4 Heavy duty screw-in wall anchors are included.
- 2-3 Mounting brackets installed on the rear of the mirror that slide into the cross-bars on the aluminum frame, allowing the mirror to be mounted after the frame has been installed

ILLUMINATION

- LED Strip: 40 LEDs per ft
- 8213 Lumens
- 50,000 hours life expectancy
- 12/1/
- 6000K standard (3000K available)
- CRI: 92

ELECTRICAL

- 120V
- IP67 - UL 8750
- Non-dimmable

CODE COMPLIANCE

- cETLus Listed
- Meets UL Requirements

WARRANTY

- 5 Years

ORDERING INFORMATION

CATALOG #	Watts	Lumens	Voltage	Temp
MM23-42L-120V-60K	42W	8,213 lumens	120V	6000K

Options (Factory Installed)

30K - 3000K







MM23 LED Mirror