

SPECIFICATIONS

OUTDOOR

HOUSING

- Heavy duty die cast aluminum housing
- Available in white, black, or bronze finish
- Corrosion resistant housing and hardware
- OxyShield 9-stage anti-oxidation process
- Silicone rubber gasket

ELECTRICAL

- QT (Quad-Tap) - 120-277V
- 120V
- 2kV surge protection standard
- Operating Temperature: -22°F (-30°C) - 122°F (50°C)
- 50,000 Hours @ L₇₀

OPTICAL SYSTEM

- Impact resistant glass lens
- CRI: 80
- Available in 3000K and 4000K
- 1900 Lumens
- Offered with a photocell or motion sensor
- 50° Beam Angle
- 20W
- Adjustable angle from 0-90°

MOUNTING

- Mounts flush on wall or 4" round weatherproof box

CODE COMPLIANCE

- cETLus Listed for Wet Locations
- Meets UL Requirements
- IP65 Rated
- T20/T24 Approved
- RoHS Compliant
- FCC Compliant

WARRANTY

- 5 Year



OSL-SA LED Security Light

ORDERING INFORMATION

CATALOG #	Description
OSL-SA-S-20L-QT-*#	Square Head, 20W, 1900 lumens, 120-277V
OSL-SA-S-20L-120V-*#-OCS	Square Head, 20W, 1900 lumens, 120V, Occupancy Sensor
OSL-SA-R-20L-QT-*#	Round Head, 20W, 1900 lumens, 120-277V
OSL-SA-R-20L-120V-*#-OCS	Round Head, 20W, 1900 lumens, 120V, Occupancy Sensor

*Specify CCT: **30K**, **40K**

#Specify Housing Color: **BK** - Black, **WH** - White, **BZ** - Bronze