

SPECIFICATIONS

MULTI-FAMILY

HOUSING

- Steel Housing
- .040" Steel cap with slots for direct mounting to junction box for surface mount
- 3 screws on the bottom of cap secure cylinder body to cap
- .040" steel body with 3 keyhole slots allowing body to be installed into cap
- Spring brackets accept torsion wing trim springs
- 4 butterfly clips accommodated for spring-less trims
- Black or White finishes available

OPTICAL SYSTEM

- COB LED
- Triac or 0-10V Dimming
- Beam spreads: 38° Spot, 56° Narrow Flood, 72° Flood
- 2700K - 4000K
- CRI>90

ELECTRICAL

- Quad Tap (QT) - 120-277V
- 120V
- 0-10V Dimming
- 50,000 hours @ L₇₀

MOUNTING

- Surface/wall, Stem or cable mount
- 8' of cable included and 5-wire cable for power and dimming
- Includes a swivel canopy and 7' of internally threaded rod
- Compatible with sloped ceilings with a pitch of 1/12 to 10/12

CODE COMPLIANCE

- cULus Listed for Damp Locations
- Energy Star Certified
- FCC Compliant
- RoHS Compliant

WARRANTY

- 5 Year



PND80-NR LED Cylinder

ORDERING INFORMATION

CATALOG#	Wattage	Driver	CCT	Housing	Mounting	Reflector
PND80-NR	11L (900 Lm)	120V	27K	BK (Black)	ST (Stem)	BB (Black/Black)
	16L (1500 Lm)	QT	30K	WH (White)	CB (Cable)	BW (Black/ Matte White)
	24L (2500 Lm)		35K		SM (Surface)	CC (Clear/Clear)
	36L (3500 Lm)		40K		WM (Wall)	CB (Diffused Clear/Black)
	44L (4500 Lm)					CD (Diffused Clear/Diffused)
	58L (5500 Lm)					CW (Diffused Clear/Matte White)
						HB (Haze/Black)
						HW (Haze/Matte White)
						HH (Haze/Haze)
						WW (Matte White/Matte White)

OPTIONS (Factory Installed)

- EM - Emergency Battery

